FK Machinery®
BY KOŁASZEWSKI

2026

PRODUCT CATALOG

POWER
in Precision *Efficiency in Every Equipment*

from Poland
to the world

POWER
in Precision Efficiency in Every Equipment

Global presence – FK Machinery products are used today across **Europe, the USA, New Zealand and many other countries**

50 years
The company celebrates 50 years of operation and focuses on building an international brand

2024

2019

The FK Machinery brand is established – a modern approach to sales and communication

Expansion of the product range – production of attachments for front loaders, telehandlers, skid steer loaders, municipal machinery and tractor-mounted concrete mixers

Implementation of proprietary solutions – development of in-house designs and innovative projects

Investment in technology and expansion of a modern machine park

2000

Lata 80.-90.

Development of agricultural machinery components and systematic strengthening of the company's position on the domestic market

Lech Kołaszewski
establishes a small metal workshop focused on quality and reliability

1974

Driven by passion
Built to perfection

FK Machinery - From a small metal workshop to a global company

The year 1974.

- ABBA's breakthrough with "Waterloo"
- Elvis Presley's final concert tour
- the FIFA World Cup in West Germany
- the premiere of The Godfather Part II
- the launch of the Voyager program

It was at that time that our father, Lech Kołaszewski, established his own metal workshop.

From passion, hands-on work and belief in quality and people begins the journey that today leads us to all continents.

Times were difficult. A shortage economy prevailed – almost everything was lacking. Tools, materials, parts... everything had to be obtained independently, improvised and built from scratch.

However, our father had the soul of an inventor. He could create something out of nothing.

He designed and built his solutions himself, from the very beginning focusing on solid craftsmanship and striving for perfection in every detail that left his hands.

Over time, the workshop grew. From a small workshop, a company was created that not only became a leader in the production of agricultural machinery components, but also began to set standards in the engineering industry. With growth came investments – in new technologies, modern machinery and proprietary design solutions.

Throughout all these years, both our father – Lech Kołaszewski – and we, his children who now manage the company, have been guided by one principle:

"If you do something – do it well."

We have been, we are and we will remain consistent in this.

Thanks to this philosophy and a strong belief in people, a small metal workshop has transformed into FK Machinery – a European brand delivering the highest quality at every stage of production.

From Bytów to the world.
FK Machinery - a global brand

We started in the small town of Bytów. Today, we are present on all continents, operating in 50 countries - not only in Europe, but also in the United States and New Zealand. We employ over 170 people – engineering enthusiasts, skilled technicians and experienced sales representatives.

The headquarters of FK Machinery is located in northern Poland, in Bytów, near Gdańsk. We operate one of the most modern machinery parks in the region. In our daily production, we use advanced technologies – including laser cutting, robotic welding and a fully automated powder coating line – ensuring precise fit and durability of every component.

Thanks to full production independence, we carry out the entire process – from design and prototyping to final assembly, finishing and testing – entirely in-house, maintaining full control over quality and minimizing lead times.

Power in Precision. Efficiency in Every Equipment, how reliability is built

Regardless of who our customers are, what they specialize in and the scale of their operations, we provide all of them with well-thought-out, reliable products of excellent quality. We continuously refine them in line with the Power in Precision. Efficiency in Every Equipment philosophy.

Our slogan reflects our approach. We strive for excellence, with a particular focus on three key areas:

FK Machinery – on all continents



2017 UK
2018 AUSTRIA
2019 ITALY, FRANCE
2020 IRELAND, ICELAND
2021 NORWAY, SWEDEN
2022 AUSTRALIA, NEW ZEALAND
2023 CHILE, CZECH REPUBLIC
2024 SPAIN

01 Knowledge and know-how

Over 50 years of experience and a broad portfolio allow us to respond precisely to specific needs. We prove this through our products – their design, engineering solutions, high build quality and operational precision. We focus on innovation, durability and refined technical solutions that genuinely improve efficiency.

02 Our contribution

At FK Machinery, we believe that technology only makes sense when it supports people – helping them in their everyday work and responding to the needs of modern agriculture. For us, the farmer is a hero of everyday life, which is why we create solutions that support efficient business operations and help those who focus on growth and specialization. Our equipment, refined in terms of precision and durability, ensures reliability in daily work. It enables better resource management, minimizing losses and maximizing yields regardless of natural conditions and seasons. This is our definition of sustainable agriculture: achieving more with less effort, thanks to intelligent machinery.

03 Relationships

We understand the challenges our customers face every day. That is why we place great emphasis on building trust and satisfaction. Our technologists, designers, engineers and sales teams support our partners at every stage – guiding them and helping them choose the most effective solutions.

PRO Line Special equipment section for the truly demanding

We consistently expand our product range with variants requested by our customers. Currently, our catalogue includes **over 250 models** – from grapples and forks to specialized buckets and ploughs – tailored to the needs of modern farms and machine fleets. One of our key strengths is the wide range of customization options and the flexibility to adapt mounting systems to **over 600 types of machines.**

In response to the growing demands of modern agriculture, we have also developed a premium product line. **PRO Line** is designed for intensive use, ready to deliver efficient performance both in large enterprises and smaller farms. Products from the **PRO Line** ensure maximum efficiency and time savings, allowing users to increase their productivity.

SWEEPER MAXI TANK BRUSH HYDRO p. 81

PRO Line

FOREST RAKE WITH GRAB p. 63

PRO Line

SNOW PLOUGH FALCON p. 71

PRO Line

ELECTRIC BALE UNROLLER PLUS p. 56

PRO Line

CHOPPER BUCKET p. 58

PRO Line

SELF LOADING BALE WRAPPER p. 59

PRO Line

BUCKET FOR BEDDING MAXI POWER p. 54

PRO Line

MIXER WITH ELECTRIC MOTOR 1200 p. 76

PRO Line

MANURE FORK WITH GRAB MAXI VISION p. 28

PRO Line

SILAGE CUTTER WITH FORKS MAXI POWER p. 49

PRO Line

BUCKET WITH SILAGE DEFACER VOLUME p. 52

PRO Line

GRASS FORKS VARIO GOLIAT p. 26

PRO Line

BUCKET 4in1 MAXI p. 41

PRO Line

BUCKET FOR SILAGE GOLIAT p. 46

PRO Line

HIGH TIP BUCKET MAXI p. 43

PRO Line

VERTICAL BALE GRAPPLE MAXI p. 24

PRO Line

Certificates

TÜV SÜD
ISO 9001:2015

TÜV SÜD Management Service

CERTIFICATE

The Certification Body
of TÜV SÜD Management Service GmbH
certifies that

KOŁASZEWSKI

"Kołaszewski" Sp. z o.o.
ul. Lęborska 22
77-100 Bytów
Poland

has established and applies
a Quality Management System for

Manufacturing and selling of
steel goods, welded and powder painted.

An audit was performed, Order No. 73440178.
Proof has been furnished that the requirements
according to

DIN EN ISO 9001:2015

are fulfilled.
The certificate is valid from 2023-06-20 until 2026-06-19.
Certificate Registration No.: 12 100 40914 TMS.

Head of Certification Body
Munich, 2023-05-24

TÜV SÜD Management Service GmbH • Zertifizierungsstelle • Ridlerstrasse 57 • 80339 München • Germany
www.tuvsud.com/de-certificate-validity-check

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

UDT-CERT
ISO 3834-2:2021-09
QUALITY IN WELDING

CERTYFIKAT

Certificate
Nr/No. CSW/1310/2025

Jednostka Certyfikująca Systemy Zarządzania UDT-CERT
UDT-CERT Management Systems Certification Body

poświadcza, że firma:
certifies that the company:

"KOŁASZEWSKI" SPÓŁKA Z O. O.

UL. LĘBORSKA 22, 77-100 BYTÓW

wdrożyła oraz stosuje wymagania jakości w spawalnictwie zgodnie z normą
has implemented and maintains quality requirements in welding system in compliance with

PN-EN ISO 3834-2:2021-09

Zakres certyfikacji według załącznika.
Scope of certification in the annex.

Data udzielenia certyfikacji: Date of certification granting:	02.12.2025
Cykl certyfikacji ważny: Certification cycle validity:	od/from 02.12.2025 do/to 01.12.2028

PCA AC 078

Dyrektor Departamentu Certyfikacji
i Oceny Zgodności
Director of Certification and Conformity
Assessment Department
wz. Aneta Głuszek

Warszawa, dn. 02.12.2025

www.udt.gov.pl Urząd Dozoru Technicznego, 02-353 Warszawa, ul. Szczęśliwicka 34 22 57 22 100

EAGLE

eVision 1530 F12.0

eVa

EAGLE

AD-SERVO40400
DURMA

DURMA

QUICK LOAD SERVO 105

DEMATEC

DOOSAN
PUMA 3100ULY

TruLaser Tube 5000



STANDARD COLORS

RAL 5011 | RAL 7035 | RAL 3000 | RAL 1002 | RAL 1037 | RAL 2003 | RAL 7021 | RAL 9005

LEGEND OF ICONS

BALE DIAMETER

SQUARE BALE DIAMETER


NUMBER OF TINES

CAPACITY

VOLUME

COVER

COVER

SURFACE AREA

NUMBER OF FORKS

WEIGHT

SIDE

BAR

RIB

STEEL BLADE

RUBBER BLADE

PRESSURE FLOW

ELECTRIC MOTOR

HYDRAULIC MOTOR

ROTATION SPEED

ROTATION SPEED

RATIO

STEEL ON SIDE CUTTING EDGE

TEETH MODEL

FRAME

TILT

SHELL

BOTTOM



PIPE DIMENSIONS

VALVE DESCRIPTION

OVERFLOW VALVE VMP - pressure relief valves are used in hydraulic systems to limit the system pressure to a specific set level. If this set level is reached, the pressure relief valve responds and feeds the excess flow from the system back to the tank.

HYDRAULIC LOCK VALVE VBPDE - is designed to lock a hydraulic cylinder and prevent it from drifting due to hydraulic leak from a directional control valve being in the neutral position or worn hydraulic valves or even a hose failure. This valve needs an oil flow signal to unlock the flow.

FLOW DIVIDER VALVE DFL - is a hydraulic device that, as the name implies, separates flow into two or more parts. This lets a single pump simultaneously power more than one circuit.

DOUBLE OVERCENTER VALVE VBCD - overcenter valve prevents the actuator running ahead of the pump due to the load-induced energy, thereby eliminating cavitation in the actuator and loss of control.

TRACTOR LINKAGE TRIANGLE CAT. 0 15

TRACTOR LINKAGE TRIANGLE CAT. I 15

TRACTOR LINKAGE TRIANGLE CAT. II 15

A FRAME TRACTOR LINKAGE CAT. I, II, III 15

LIGHTWEIGHT EURO ADAPTER 16

HEAVYWEIGHT EURO ADAPTER 16

HEAVYWEIGHT EURO ADAPTER HYDRAULIC 16

WEIDEMANN ADAPTER 16

JCB Q-FIT ADAPTER 16

MANITOU ADAPTER 17

MAILLEUX MX ADAPTER 17

VOLVO L70 ADAPTER 17

THREE-POINT HITCH ADAPTER CAT. II 17

SKID STEER ADAPTER 17

SMS ADAPTER 18

MERLO ADAPTER 18

CLAAS SCORPION ADAPTER 18

VOLVO L30 / LIEBHERR ADAPTER 18

KRAMER ADAPTER 18

MATBRO ADAPTER 19

GIANT ADAPTER 19

EURO SMS ADAPTER 19

FEM3 THREE-POINT HITCH ADAPTER CAT. I, II, III 19

AVANT ADAPTER 19

VOLVO L20-L25 ADAPTER 20

FAUCHEUX GRIS MX ADAPTER 20

LIGHTWEIGHT EURO ADAPTER LEHNHOFF MS03 SYMLOCK 20

HEAVYWEIGHT EURO ADAPTER LEHNHOFF MS08 SYMLOCK 20

BALE FORK – 2 TINES 21

BALE FORK REINFORCED – 3 TINES 21

BALE FORK – 4 TINES 21

BALE FORK ADJUSTABLE – 4 TINES 21

FOLDABLE BALE FORK 21

BALE FORK FOR TELESCOPIC LOADERS 22

BALE FORK + BIG BAG HOOK 22

BALE TRANSPORTER – MECHANICAL 22

BALE TRANSPORTER – HYDRAULIC 22

MICRO BALE GRAPPLE 23

SMART BALE GRAPPLE 23

ROUND BALE GRAPPLE 1 HYDRAULIC CYLINDER 23

SQUARE BALE GRAPPLE 24

VERTICAL BALE GRAPPLE 24

VERTICAL BALE GRAPPLE MAXI 24

MANURE FORKS MIKRO 25

MANURE FORKS STANDARD 26

MANURE FORKS MAXI 26

MANURE FORKS TELESCOPE 26

GRASS FORKS VARIO GOLIAT 26

MANURE FORK WITH GRAB MICRO 27

MANURE FORK WITH GRAB MINI 27

MANURE FORK WITH GRAB STANDARD 27

MANURE FORK WITH GRAB MAXI 28

MANURE FORK WITH GRAB MAXI VISION 28

MANURE RUBBER BLADE – RIGID 28

MANURE RUBBER BLADE HYDRAULIC 28

PALLET FORKS 0.6 T 29

PALLET FORKS 1.6 T 29

PALLET FORKS 2.0 T 30

PALLET FORKS XL 30

HYDRAULIC PALLET FORKS 2,5T 30

HYDRAULIC PALLET FORKS 4,2T 30

PALLET FORKS ROTATING 1,6 T 31

PALLET FORKS ROTATING 1,6 T + UPPER ARM 31

PALLET FORKS ROTATING 2,5 T 31

PALLET FORKS ROTATING 2,5 T + UPPER ARM 32

BIG BAG TRANSPORTER 32

TRANSPORT BOX 32

HYDRAULIC TRANSPORT BOX 32

FORKLIFT WORK PLATFORM 33

FORKLIFT WORK PLATFORM WITH A CERTIFICATE 33

FORKLIFT WORK PLATFORM ELEVATED VERSION 33

BUCKET NANO 34

BUCKET MICRO 34

BUCKET MINI 35

BUCKET MINI VOLUME 35

BUCKET STANDARD 35

BUCKET VOLUME 35

BUCKET FOR STONE 36

BUCKET FOR STONE WITH GRIPPER 36

BUCKET FOR ROOT CROP MINI 37

BUCKET FOR ROOT CROP STANDARD 37

BUCKET FOR ROOT CROP MAXI 37

BUCKET FOR ROOT CROP (POTATO) 37

BUCKET FOR GRAIN 38

STANDARD CONSTRUCTION BUCKET 38

BUCKET HEAVY DUTY MINI 39

BUCKET HEAVY DUTY STANDARD 39

BUCKET HEAVY DUTY VOLUME 39

BUCKET HEAVY DUTY MAXI 39

GENERAL PURPOSE LOADING BUCKET MINI 40

GENERAL PURPOSE LOADING BUCKET STANDARD 40

GENERAL PURPOSE LOADING BUCKET VOLUME 40

GENERAL PURPOSE LOADING BUCKET MAXI 40

BUCKET 4 IN 1 MINI 41

BUCKET 4 IN 1 STANDARD 41

BUCKET 4 IN 1 MAXI 41

GRADING BUCKET MINI 42

GRADING BUCKET STANDARD 42

GRADING BUCKET MAXI 42

BUCKET FOR COBBLESTONE MINI 42

BUCKET FOR COBBLESTONE STANDARD 42

HIGH TIP BUCKET WITH GRAB 43

HIGH TIP BUCKET 43

HIGH TIP BUCKET VOLUME 43

HIGH TIP BUCKET MAXI 43

BUCKET WITH GRAB MICRO 44

BUCKET WITH GRAB MINI 44

BUCKET WITH GRAB STANDARD 44

BUCKET WITH GRAB MAXI 44

BUCKET FOR SILAGE MINI 45

BUCKET FOR SILAGE STANDARD 45

BUCKET FOR SILAGE MAXI 46

BUCKET FOR SILAGE MAXI TELESCOPIC 46

BUCKET FOR SILAGE GOLIAT 46

BUCKET FOR RECYCLING 46

SILAGE CUTTER MULTI 3 IN 1 47

SILAGE CUTTER WITH FORKS 48

SILAGE CUTTER WITH FORKS BOLT-ON TEETH 48

SILAGE CUTTER WITH BUCKET 48

SILAGE CUTTER WITH BUCKET BOLT-ON TEETH 48

SILAGE CUTTER WITH FORKS MAXI POWER 49

SILAGE CUTTER WITH BUCKET MAXI POWER 49

BUCKET WITH FEEDING AUGER 50

BUCKET WITH SILAGE DEFACER VOLUME 50

BUCKET WITH SILAGE DEFACER 51

BUCKET WITH SILAGE DEFACER VOLUME 51

BUCKET WITH FEEDING AUGER AND GRAB 52
BUCKET WITH FEEDING AUGER AND GRAB VOLUME 52
BUCKET WITH SILAGE DEFACER 52
BUCKET FOR BEDDING MINI 53
BUCKET FOR BEDDING UNIVERSAL 53
BUCKET FOR BEDDING MAXI 54
BUCKET FOR BEDDING MAXI POWER 54
BUCKET FOR BEDDING WITH HYDRAULIC CHUTE OPENING DISCHARGE 54
BALE UNROLLER 56
BALE UNROLLER WITH ROTOR FOR BEDDING 56
ELECTRIC BALE UNROLLER BASIC 56
ELECTRIC BALE UNROLLER PLUS 56
BALE CUTTER 57
BALE CUTTER BOLT-ON TEETH 57
CHOPPER BUCKET 58
SELF LOADING BALE WRAPPER 59

LOG GRAPPLE R27 60
LOG GRAPPLE R34 60
LOG GRAPPLE R49 60
WOOD GRIPPER FOR PALLET TRUCK 61
WOOD GRIPPER 1-ARM 61
WOOD GRIPPER 2-ARM 61
WOOD GRIPPER STANDARD 62
WOOD GRIPPER MAXI 62
WOOD GRIPPER GOLIAT 62
WOOD GRIPPER WITH FORKS 62
FOREST RAKE 63
FOREST RAKE PROFILED FRAME 63
FOREST RAKE WITH GRAB 63
ACTIVE FOREST PLOUGH 64
ROOT RIPPER 64

SPREADER SAND PADAWAN 65
SPREADER SAND MASTER 65
SNOW PLOUGH STRAIGHT COMMUNAL 68
SNOW PLOUGH VARIO COMMUNAL 68
SNOW PLOUGH STRAIGHT LIGHTWEIGHT 68
SNOW PLOUGH VARIO LIGHTWEIGHT 68
SNOW PLOUGH STANDARD 70
SNOW PLOUGH VARIO STANDARD 70
SNOW PLOUGH STRAIGHT HEAVYWEIGHT 70
 SNOW PLOUGH VARIO HEAVYWEIGHT 70
 SNOW PLOUGH FALCON 71

 SNOW PLOUGH X-WING 71
 DOZER BLADE SUPERLIGHT FOR TRACTOR REAR 73
 DOZER BLADE LIGHTWEIGHT FOR TRACTOR REAR 73
 DOZER BLADE HEAVYWEIGHT FOR TRACTOR REAR 73
 DOZER BLADE HEAVYWEIGHT FOR TRACTOR REAR TILTED 73

 MIXER WITH PTO DRIVE 600 74
 MIXER WITH PTO DRIVE 800 74
 MIXER WITH PTO DRIVE 1200 74
 MIXER WITH HYDRAULIC DRIVE 600 75
 MIXER WITH HYDRAULIC DRIVE 800 75
 MIXER WITH HYDRAULIC DRIVE 1200 75
 MIXER COMBI (PTO AND HYDRAULICS) 600 75
 MIXER COMBI (PTO AND HYDRAULICS) 800 75
 MIXER COMBI (PTO AND HYDRAULICS) 1200 75
 MIXER WITH ELECTRIC MOTOR 600 76
 MIXER WITH ELECTRIC MOTOR 800 76
 MIXER WITH ELECTRIC MOTOR 1200 76
 MIXER WITH ELECTRIC MOTOR LOW TYPE 600 76
 MIXER WITH ELECTRIC MOTOR LOW TYPE 800 76
 MIXER WITH ELECTRIC MOTOR LOW TYPE 1200 76
 SELF-LOADER 600, 800, 1200 77

BUCKET CONCRETE MIXING 78

SWEEPER MINI BASIC 80

SWEEPER BASIC 80

SWEEPER MAXI BASIC 80

SWEEPER MINI TANK 80

SWEEPER TANK 80

SWEEPER MAXI TANK 80

SWEEPER MINI TANK BRUSH 81

SWEEPER TANK BRUSH 81

SWEEPER MAXI TANK BRUSH 81

SWEEPER MINI TANK BRUSH HYDRO 81

SWEEPER TANK BRUSH HYDRO 81

SWEEPER MAXI TANK BRUSH HYDRO 81

HEAVY FIELD HARROW 4 m 4 ROWS HYDRAULIC 83

HEAVY FIELD HARROW 5,1 m 4 ROWS HYDRAULIC 83

HEAVY FIELD HARROW 6,3 m 4 ROWS HYDRAULIC 83

HEAVY FIELD HARROW 8 m. 4 ROWS HYDRAULIC 83

EXCAVATOR BUCKETS

DIGGING BUCKET 1-1,9T 85

DIGGING BUCKET 1,9-2,6 T 85

DIGGING BUCKET 2,6-3,5 T 85

DIGGING BUCKET 3,5-5t 85

DIGGING BUCKET 5-6t 85

DIGGING BUCKET 6-8,5t 86

DIGGING BUCKET 8,5-10t 86

DIGGING BUCKET 10-12T 86

DIGGING BUCKET 12-14T 86

DIGGING BUCKET 14-18T 86

SKELETON BUCKETS

SKELETON BUCKET 1-1,9t 87

SKELETON BUCKET 1,9-2,6t 87

SKELETON BUCKET 2,6-3,5t 87

SKELETON BUCKET 3,5-5t 87

SKELETON BUCKET 5-6t 87

SKELETON BUCKET 6-8,5t 88

SKELETON BUCKET 8,5-10t 88

SKELETON BUCKET 10-12T 88

SKELETON BUCKET 12-14T 88

SKELETON BUCKET 14-18T 88

SORTING BUCKETS

SORTING BUCKET 5-6T 89

 SORTING BUCKET 6-8,5T 89

 SORTING BUCKET 8,5-10T 89

 SORTING BUCKET 10-12T 89

 SORTING BUCKET 12-14T 89

 SORTING BUCKET 14-18T 90

TRENCHING BUCKETS

 TRENCHING BUCKET 1-1,9T 91

 TRENCHING BUCKET 1,9-2,6T 91

 TRENCHING BUCKET 2,6-3,5T 91

 TRENCHING BUCKET 3,5-5T 91

 TRENCHING BUCKET 5-6T 91

 TRENCHING BUCKET 6-8,5T 92

 TRENCHING BUCKET 8,5-10T 92

 TRENCHING BUCKET 10-12T 92

 TRENCHING BUCKET 12-14T 92

 TRENCHING BUCKET 14-18T 92

DITCHING BUCKETS

 DITCHING BUCKET 1,9-2,6T 93

 DITCHING BUCKET 2,6-3,5T 93

 DITCHING BUCKET 3,5-5T 93

 DITCHING BUCKET 5-6T 93

 DITCHING BUCKET 6-8,5T 93

 DITCHING BUCKET 8,5-10T 94

DITCHING BUCKET 10-12T 94
DITCHING BUCKET 12-14T 94
DITCHING BUCKET 14-18T 94

HYDR. TILT DITCHING BUCKETS

HYDRAULIC TILTING DITCHING BUCKET 1,9-2,6T 95
HYDRAULIC TILTING DITCHING BUCKET 2,6-3,5T 95
HYDRAULIC TILTING DITCHING BUCKET 3,5-5T 95
HYDRAULIC TILTING DITCHING BUCKET 5-6T 95
HYDRAULIC TILTING DITCHING BUCKET 6-8,5T 95
HYDRAULIC TILTING DITCHING BUCKET 8,5-10T 96
HYDRAULIC TILTING DITCHING BUCKET 10-12T 96
HYDRAULIC TILTING DITCHING BUCKET 12-14T 96
HYDRAULIC TILTING DITCHING BUCKET 14-18T 96

SCANDINAVIAN BUCKETS

SCANDINAVIAN BUCKET 3,5-5T 97
SCANDINAVIAN BUCKET 5-6T 97
SCANDINAVIAN BUCKET 6-8,5T 98
SCANDINAVIAN BUCKET 8,5-10T 98
SCANDINAVIAN BUCKET 10-12T 98
SCANDINAVIAN BUCKET 12-14T 98
SCANDINAVIAN BUCKET 14-18T 98

HYDR. SCANDINAVIAN BUCKETS

HYDRAULIC SCANDINAVIAN BUCKET 3,5-5T 99
HYDRAULIC SCANDINAVIAN BUCKET 5-6T 99
HYDRAULIC SCANDINAVIAN BUCKET 6-8,5T 100
HYDRAULIC SCANDINAVIAN BUCKET 8,5-10T 100
HYDRAULIC SCANDINAVIAN BUCKET 10-12T 100
HYDRAULIC SCANDINAVIAN BUCKET 12-14T 100
HYDRAULIC SCANDINAVIAN BUCKET 14-18T 100

TAPERED DITCHING BUCKETS

TAPERED DITCHING BUCKET 1-3,5T 101
TAPERED DITCHING BUCKET 3,5-6T 101
TAPERED DITCHING BUCKET 6-10T 101
TAPERED DITCHING BUCKET 10-14T 101
TAPERED DITCHING BUCKET 14-18T 101

TAPERED DITCHING BUCKETS HYDR.

HYDRAULIC TAPERED DITCHING BUCKET 1-3,5T 102
HYDRAULIC TAPERED DITCHING BUCKET 3,5-6T 102
HYDRAULIC TAPERED DITCHING BUCKET 6-10T 102
HYDRAULIC TAPERED DITCHING BUCKET 10-14T 102
HYDRAULIC TAPERED DITCHING BUCKET 14-18T 102

RIPPERS

RIPPER 1-1,9T 103
RIPPER 1,9-3,5T 103
RIPPER 3,5-6T 103
RIPPER 6-12T 103
 RIPPER 12-18T 103

RIPPERS SAW

 RIPPER SAW 1-1,9T 104
 RIPPER SAW 1,9-3,5T 104
 RIPPER SAW 3,5-6T 104
 RIPPER SAW 6-12T 104
 RIPPER SAW 12-18T 104

GRADING BEAMS

 GRADING BEAM 1,9-6T 105
 GRADING BEAM 6-14T 105
 GRADING BEAM 14-24T 105

HYDRAULIC GRADING BEAMS

 HYDRAULIC GRADING BEAM 1,9-6T 106
 HYDRAULIC GRADING BEAM 6-14T 106
 HYDRAULIC GRADING BEAM 14-24T 106

EXCAVATOR PALLET FORKS

 PALLET FORKS 1,6T 107
 PALLET FORKS 2,0T 107
 PALLET FORKS 2,5T 107
 PALLET FORKS 2,5T HYDRAULIC 107

ADAPTERS

We offer a wide range of adapters, quick couplers, connectors. In total, our database contains over 600 of mountings for various type of loaders. All inquiries of a specific adapter please send to our commercial department.

TRACTOR LINKAGE TRIANGLE CAT. 0

M115



SPECIFICATION

- tractor linkage triangle
- three-point hitch cat. 0

TRACTOR LINKAGE TRIANGLE CAT. I

M353



SPECIFICATION

- tractor linkage triangle
- three-point hitch cat. I

TRACTOR LINKAGE TRIANGLE CAT. II

M223



SPECIFICATION

- tractor linkage triangle
- three-point hitch cat. II

A FRAME TRACTOR LINKAGE CAT. I, II, III

M97



SPECIFICATION

- implement triangle attachment

LIGHTWEIGHT EURO ADAPTER

RA24





SPECIFICATION

- mechanical version

1500 kg | 50 - 130 kg

HEAVYWEIGHT EURO ADAPTER

RA18





SPECIFICATION

- mechanical version

3000 kg | 75 - 160 kg

HEAVYWEIGHT EURO ADAPTER - HYDRAULIC

RA18B







SPECIFICATION

- hydraulic version

3000 kg | 75 - 160 kg

WEIDEMANN ADAPTER

RA00





SPECIFICATION

- mechanical version

2500 kg | 50 - 130 kg

JCB Q-FIT ADAPTER

RA02





SPECIFICATION

- mechanical version

3000 kg | 50 - 130 kg

MANITOU ADAPTER

RA07



SPECIFICATION

- mechanical version

4500 kg | 70 - 150 kg

MAILLEUX MX ADAPTER

RA09



SPECIFICATION

- mechanical version

2300 kg | 50 - 130 kg

VOLVO L70 ADAPTER

RA17



SPECIFICATION

- mechanical version

2500 kg | 128 - 200 kg

THREE-POINT HITCH ADAPTER CAT. II

RA19



SPECIFICATION

- mechanical version
- lower pin lock

2500 kg | 70-150 kg

SKID STEER ADAPTER (BOBCAT)

RA20



SPECIFICATION

- mechanical version

2000 kg | 75 - 160 kg

SMS ADAPTER

RA22



SPECIFICATION

- mechanical version

2300 kg

50 - 100 kg

MERLO ADAPTER

RA31



SPECIFICATION

- mechanical version

4000 kg

80 - 160 kg

CLAAS SCORPION ADADPTER

RA35



SPECIFICATION

- mechanical version

3500 kg

105 - 155 kg

VOLVO L30 / LIEBHERR ADAPTER

RA36



SPECIFICATION

- mechanical version

2500 kg

85 - 135 kg

KRAMER ADAPTER

RA37



SPECIFICATION

- mechanical version

2500 kg

80 - 160 kg

MATBRO ADAPTER

RA39



SPECIFICATION

- mechanical version

2500 kg | 90 - 150 kg

GIANT ADAPTER

RA44



SPECIFICATION

- mechanical version

2000 kg | 80-120 kg

EURO SMS ADAPTER

RA46



SPECIFICATION

- wersja mechaniczna

3000 kg | 68 - 130 kg

FEM III & TUZ KAT. I-III ADAPTER

RA48



SPECIFICATION

- mechanical version

2500 kg | 80-160 kg

AVANT ADAPTER

RA58



SPECIFICATION

- mechanical version

1250 kg | 30 - 80 kg

VOLVO L20 - L25 ADAPTER

RA59



SPECIFICATION

- mechanical version

2500 kg | 62 - 140 kg

FAUCHEUX GRIS MX ADAPTER

RA64



SPECIFICATION

- mechanical version

2500 kg | 60 - 110 kg

LIGHTWEIGHT EURO - LEHNHOFF MS03 SYMLOCK ADAPTER

RA24_MS03



SPECIFICATION

- mechanical version

1500 kg | 99 kg

HEAVYWEIGHT EURO - LEHNHOFF MS08 SYMLOCK ADAPTER

RA18_MS08



SPECIFICATION

- mechanical version

3000 kg | 136 kg

BALE FORK – 2 TINES

UBF2T

2 pcs | 1100 kg | 65 kg



SPECIFICATION

- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines

BALE FORK REINFORCED – 3 TINES

UBF3T

3 pcs | 1500 kg | 78 kg



SPECIFICATION

- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines

BALE FORK – 4 TINES

UBF4T

4 pcs | 1700 kg | 110 kg



SPECIFICATION

- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines

BALE FORK ADJUSTABLE – 4 TINES

UBF4W

4 pcs | 1500-2500 kg | 159-188 kg



SPECIFICATION

- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines
- height adjustment of the support
- bushing to M22

OPTIONS

- UBF4WB- bushing to M28

FOLDABLE BALE FORK

UBF5F

5 pcs | 2500 kg | 160 kg



SPECIFICATION

- adjustable profiles
- foldable hydraulic forks
- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines
- height adjustment of the support
- bushing to M22

BALE FORK FOR TELESCOPIC LOADERS

XLUBFT

10 pcs

3000 kg

205 kg



SPECIFICATION

- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines – L1200 M22 in the lower row

BALE FORK + BIG BAG HOOK

UVF5

UVF3



7-9 pcs

2500 kg

131-150 kg



SPECIFICATION

- options: fork or Big Bag hook
- versatile usage
- tines reinforced with tapered bushings
- high quality forged tines
- working range adjustment

OPTIONS

- extra tine L-1100 M22
- extra tine L-632

INDEX	WIDTH	OPTIONS
UVF3	1200 mm	extendable profile with spikes
UVF5	1400 mm	extendable profile with spikes
UVF3-B	1200 mm	hook BIG BAG
UVF5-B	1400 mm	hook BIG BAG

BALE TRANSPORTER – MECHANICAL

UBTM

1,2 - 1,8 m

1000 kg

130 kg

UBTM TUZ KAT. II



SPECIFICATION

- thick material tube
- versatile usage
- working width adjustment

OPTIONS

- optional forged tine L-1100 M22
- optional profile pallet fork



BALE TRANSPORTER – HYDRAULIC

UBTH

0,8 - 1,8 m

1000 kg

176 kg



SPECIFICATION

- suitable for wrapped bales and straw bales
- large working width range
- pipes rotating during operation
- easy access to greasing nipples

MICRO BALE GRAPPLE

UBGN



0,8-1,6 m	950 kg	155 kg	63 x 3 mm

SPECIFICATION

- 63x3 mm thick pipe arm
- design to maximize lifting height
- 1 hydraulic cylinder

OPTIONS

- pressure relief valve - VMP
- hydraulic lock - VBPDE

SMART BALE GRAPPLE

UBGS



0,8 - 1,6 m	1000 kg	165 kg	48 x 3 mm

SPECIFICATION

- 48x3 mm thick pipe arm
- 1 hydraulic cylinder
- optimum grip of bales of smaller diameters

OPTIONS

- pressure relief valve - VMP

ROUND BALE GRAPPLE, 1 HYDRAULIC CYLINDER

UBG

UBG2C
2 -CYLINDERS

YouTube



0,9 - 1,8 m	1000 kg	185-200 kg	63 x 3 mm

SPECIFICATION

- 63x3 thick pipe arm
- retractable stands
- 1 hydraulic cylinder
- optimum grip of bales of different diameters

OPTIONS

- pressure relief valve - VMP
- hydraulic lock - VBPDE

INDEX	NO. OF CYLINDERS	CAPACITY	WEIGHT
UBG	1	1000 kg	185 kg
UBG2C	2	1000 kg	200 kg

TRANSPORT OF BALES

PRO Line

SQUARE BALE GRAPPLE

USBG





USBS



0,8 - 2,1 m	1000 kg	300-349 kg	60 x 3 mm

SPECIFICATION

- 60x3 mm thick pipe arm
- 2 hydraulic cylinders
- Optimum bales grip of smaller diameters

OPTIONS

- flow divider valve - DFL
- pressure relief valve - VMP
- adjustment of the support

VERTICAL BALE GRAPPLE

USBV





USBV-B





2,1 - 2,8 m	1500 kg	185 kg

SPECIFICATION

- modular construction
- 1 hydraulic ram on each segment
- also suitable for round bale
- tine L-485 M10

OPTIONS

- pressure relief valve - VMP
- hydraulic lock - VBPDE

VERTICAL BALE GRAPPLE MAXI

USBV-C







2,1 - 2,8 m	2100 kg	420 kg

SPECIFICATION

- modular construction
- 1 hydraulic ram on each segment
- also suitable for round bale
- required only 1 hydraulic circuit
- tine L-485 M10
- tine L-980 M28

OPTIONS

- pressure relief valve - VMP
- hydraulic lock - VBPDE
- version with 5 tines in the arms.

MANURE FORK

MANURE FORKS MIKRO

AMMF



SPECIFICATION

- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines L-810 M22

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
AMMF100	100 cm	76 kg	0,35 m³	6
AMMF120	120 cm	85 kg	0,41 m³	7
AMMF130	130 cm	88 kg	0,45 m³	7

MANURE FORKS STANDARD

MMF



≠ 8 mm

≠ 5 mm

SPECIFICATION

- thick material tube
- tines reinforced with tapered bushings
- high quality forged tines L-810 M22

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MMF140	140 cm	90 kg	0,62 m³	8
MMF150	150 cm	95 kg	0,66 m³	8
MMF160	160 cm	100 kg	0,70 m³	9
MMF180	180 cm	110 kg	0,79 m³	9
MMF200	200 cm	120 kg	0,88 m³	10
MMF220	220 cm	130 kg	0,97 m³	11
MMF240	240 cm	140 kg	1,06 m³	12

MANURE FORKS MAXI

MMFM



≠ 8 mm

≠ 6 mm

SPECIFICATION

- thick material tube design
- tines reinforced with tapered bushings
- high quality forged tines L-1100 M22
- 2 screwed-on side tines

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MMFM170	170 cm	210 kg	1,16 m³	9
MMFM190	190 cm	226 kg	1,29 m³	10
MMFM210	210 cm	249 kg	1,43 m³	10
MMFM230	230 cm	275 kg	1,56 m³	11
MMFM250	250 cm	297 kg	1,70 m³	12
MMFM270	270 cm	316 kg	1,84 m³	13

MANURE FORKS TELESCOPE

XLMMF





SPECIFICATION

- thick material tube design
- tines reinforced with tapered bushings
- high quality forged tines
- gridded back for better visibility

OPTIONS

- extra tine L-980 M28
- extra tine L-820 M28

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLMMF180	180 cm	305 kg	1,37 m³	9
XLMMF200	200 cm	337 kg	1,52 m³	10
XLMMF220	220 cm	369 kg	1,67 m³	11
XLMMF240	240 cm	401 kg	1,82 m³	12
XLMMF260	260 cm	433 kg	1,98 m³	13
XLMMF280	280 cm	465 kg	2,13 m³	14

GRASS FORKS VARIO GOLIAT

XLMMFV





SPECIFICATION

- thick material tube design
- tines reinforced with tapered bushings
- high quality forged tines
- gridded back for better visibility
- hydraulic folded sides

OPTIONS

- extra tine L-1200 M28
- extra tine L-980 M28

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLMMFV435	435 cm	1121 kg	5,45 m³	22
XLMMFV485	485 cm	1299 kg	6,07 m³	24
XLMMFV535	535 cm	1488 kg	6,70 m³	26

MANURE FORK WITH GRAB MICRO

AFWG

≠ 8 mm | ≠ 4 mm | 0,21-0,37 m³



SPECIFICATION

- solid steel grab tines
- lower tines made of forged steel (L-810)
- 1 hydraulic cylinder
- tines reinforced with tapered bushings

OPTIONS

- pressure relief valve VMP

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
AFWG080	80 cm	88 kg	0,21 m³	4/5
AFWG100	100 cm	116 kg	0,26 m³	4/6
AFWG120	120 cm	128 kg	0,32 m³	4/7
AFWG140	140 cm	141 kg	0,37 m³	4/8

MANURE FORK WITH GRAB MINI

SFWG

≠ 8 mm | ≠ 4 mm | 0,36-0,68 m³



SPECIFICATION

- solid steel grab tines
- lower tines made of forged steel (L-810)
- 2 hydraulic cylinders, width above 1,2 m
- 4 screwed-on tines as a standard
- tines reinforced with tapered bushings

OPTIONS

- pressure relief valve VMP
- forged tines in the grab

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
SFWG090	90 cm	155 kg	0,36 m³	4/5
SFWG110	110 cm	170 kg	0,44 m³	5/6
SFWG120	120 cm	195 kg	0,48 m³	6/7
SFWG140	140 cm	210 kg	0,56 m³	7/8
SFWG150	150 cm	220 kg	0,60 m³	7/8
SFWG170	170 cm	233 kg	0,68 m³	8/9

MANURE FORK WITH GRAB

MFWG

≠ 10 mm | ≠ 5 mm | 0,77-1,32 m³



SPECIFICATION

- tines made of forged steel (L-810, L-680)
- 2 hydraulic cylinders
- 4 screwed-on tines as a standard
- tines reinforced with tapered bushings
- the widths above of 2 m – 3 hinges

OPTIONS

- pressure relief valve VMP

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MFWG140	140 cm	255 kg	0,77 m³	6/7
MFWG160	160 cm	300 kg	0,88 m³	7/8
MFWG180	180 cm	320 kg	0,99 m³	8/9
MFWG200	200 cm	340 kg	1,10 m³	9/10
MFWG220	220 cm	370 kg	1,21 m³	10/11
MFWG240	240 cm	410 kg	1,32 m³	10/11

MANURE FORK WITH GRAB MAXI

XLFWG

≠ 12 mm | ≠ 6 mm | 1,62-2,25 m³



SPECIFICATION

- tines made of forged steel (tine L-980, L-770)
- 2 hydraulic cylinders
- 4 screwed-on tines as a standard
- split jaw from the width above 2.0 m
- back with openings for better visibility

OPTIONS

- pressure relief valve VMP

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLFWG180	180 cm	470 kg	1,62 m³	8/9
XLFWG200	200 cm	500 kg	1,80 m³	9/10
XLFWG220	220 cm	530 kg	1,98 m³	10/11
XLFWG230	230 cm	550 kg	2,07 m³	10/12
XLFWG250	250 cm	580 kg	2,25 m³	12/13

MANURE FORK WITH GRAB MAXI VISION

FWGMV

≠ 12 mm | ≠ 6 mm | 1,92-2,58 m³



SPECIFICATION

- tines made of forged steel (tine L-980, L-770)
- 2 hydraulic cylinders
- 4 screwed-on tines as a standard
- split jaw from the width above 2.0 m
- skeleton construction for better vision

OPTIONS

- pressure relief valve VMP

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
FWGMV180	180 cm	495 kg	1,92 m³	8/9
FWGMV200	200 cm	529 kg	2,14 m³	9/10
FWGMV220	220 cm	560 kg	2,36 m³	10/11
FWGMV240	240 cm	588 kg	2,58 m³	11/12

MANURE RUBBER BLADE – RIGID

MRSM



SPECIFICATION

- fiber rubber board
- support foot

OPTIONS

- galvanized frame

INDEX	WIDTH	WEIGHT
MRSM150	150 cm	165 kg
MRSM170	170 cm	175 kg
MRSM200	200 cm	185 kg
MRSM220	220 cm	195 kg
MRSM240	240 cm	200 kg
MRSM260	260 cm	205 kg
MRSM300	300 cm	220 kg

MANURE RUBBER BLADE – HYDRAULIC

MRSH



SPECIFICATION

- fiber rubber board
- working angle adjustment
- overflow protection
- support foot

OPTIONS

- galvanized frame

INDEX	WIDTH	WEIGHT	WORKING WIDTH
MRSH150	150 cm	230 kg	95-150cm
MRSH170	170 cm	242 kg	105-170cm
MRSH200	200 cm	265 kg	120-200cm
MRSH220	220 cm	273 kg	130-220cm
MRSH240	240 cm	280 kg	140-240cm
MRSH260	260 cm	295 kg	150-260cm
MRSH300	300 cm	315 kg	180-300cm

LOAD TRANSPORT

PALLET FORKS 0,6 T

UPFN06



2 pcs	650 kg	55 kg

SPECIFICATION

- metal sheet bended fork 100x45x6
- frame made of S355 carbon steel
- mechanical fork width adjustment

PALLET FORKS 1,6 T

UPF16/12



2 pcs	1600 kg	165 kg

SPECIFICATION

- 80x40x1200 2,0T FEM 2A fork as a standard
- 18 mm tool steel plate
- mechanical fork width adjustment

OPTIONS

- UPF16/10 - 80x40x1000 2,0T FEM 2A fork

PALLET FORKS 2,0 T

UPF20/12



2 pcs | 2000-2500 kg | 171-185 kg

SPECIFICATION

- 80x40x1,200 2.0T FEM 2A fork as a standard
- 4 tapered bushings to attach the bale tine
- mechanical fork width adjustment

OPTIONS

- UPF20/10 - 80x40x1000 2T FEM 2A fork
- UPF25 - 100x40x1200 2,5T FEM 2A fork
- bale tine L-1100 M22
- bolt on protection frame

PALLET FORKS XL

XLPF30/16



2 pcs | 3000-5000 kg | 200-300 kg

SPECIFICATION

- 120x40x1600 3T FEM 2A fork as a standard
- mechanical fork width adjustment
- construction reinforced with c section steel channel

OPTIONS

- XLPF35/16 - 100x45x1600 3,5T FEM 3A fork
- XLPF50/16 - 125x50x1600 5T FEM 3A fork

HYDRAULIC PALLET FORKS 2,5 T

UPF25H



2 pcs | 2500 kg | 239 kg

SPECIFICATION

- synchronous fork extension
- 100x40x1200 2.5 T fork as a standard

OPTIONS

- UPF25H-C hydraulic valve enabling side shifting
- flow divider valve - DFL- Synchronous fork adjustment

HYDRAULIC PALLET FORKS 4,2 T

UPF40H



2 pcs | 4200 kg | 299 kg

SPECIFICATION

- synchronous fork extension
- 125x45x1400 4T fork as a standard

OPTIONS

- UPF40H-D hydraulic valve enabling side shifting
- flow divider valve - DFL - Synchronous fork adjustment

PALLET FORKS ROTATING 1,6 T

UPFR16



2 pcs | 1600 kg | 188 kg

SPECIFICATION

- adjustable side arm to hold the load
- 1 hydraulic cylinder
- rotation speed control
- mechanical fork width adjustment
- 80x40x1200 2,0T FEM 2A fork as a standard

PALLET FORKS ROTATING 1,6T + UPPER ARM

UPFR16-W-C



2 pcs | 2000 kg | 195 kg

SPECIFICATION

- adjustable side arm to hold the load
- 1 hydraulic cylinder
- rotation speed control
- mechanical fork width adjustment
- upper arm to hold pallet box range
  H: 570-745 mm, L: 800-1000 mm
- 80x40x1200 2,0T FEM 2A fork as a standard

PALLET FORKS ROTATING 2,5 T

UPFR25



2 pcs | 2500 kg | 305 kg

SPECIFICATION

- adjustable side arm to hold the load
- 1 hydraulic cylinder
- rotation speed control
- 100x40x1200 2,5T FEM 2A fork as a standard

PALLET FORKS ROTATING 2,5T + UPPER ARM

UPFR25-W-C

2 pcs

2500 kg

334 kg



SPECIFICATION

- adjustable side arm to hold the load
- 1 hydraulic cylinder
- rotation speed control
- mechanical fork width adjustment
- upper arm to hold pallet box range
  H: 570-745 mm, L: 800-1000 mm
- 100x40x1200 2,5T FEM 2A fork as a standard

BIG BAG TRANSPORTER

UBB

4 pcs

2000 kg

195 kg





SPECIFICATION

- adjustable arm spacing
- 4 snap hooks
- hook spacing adjustment
- stopper to prevent slipping of bigbag belts

TRANSPORT BOX

UTB

≠ 3 mm

≠ 3 mm

0,66-1,10 m³

700 kg



SPECIFICATION

- mechanical discharge
- opening rear sideboard
- fixing – three-point hitch Cat. I and II

INDEX	WIDTH	WEIGHT	VOL.
UTB120	120 cm	210 kg	0,66 m³
UTB150	150 cm	231 kg	0,83 m³
UTB180	180 cm	254 kg	0,99 m³
UTB200	200 cm	269 kg	1,10 m³

HYDRAULIC TRANSPORT BOX

UTBB

≠ 3 mm

≠ 3 mm

0,66-1,10 m³

700 kg



SPECIFICATION

- hydraulic discharge
- opening rear sideboard
- fixing – three-point hitch Cat. I and II

INDEX	WIDTH	WEIGHT	VOL.
UTBB120	120 cm	249 kg	0,66 m³
UTBB150	150 cm	273 kg	0,83 m³
UTBB180	180 cm	295 kg	0,99 m³
UTBB200	200 cm	308 kg	1,10 m³

FORKLIFT WORK PLATFORM

CKN



SPECIFICATION

- anti-slip sheet on the floor
- door with air spring
- pallet fork pockets with safety locking pin
- protective bar mesh

INDEX	WIDTH	WEIGHT
CKN130	130 cm	220 kg
CKN240	240 cm	320 kg

FORKLIFT WORK PLATFORM WITH A CERTIFICATE

CWP



SPECIFICATION

- CWP – version with a certificate and additional crush protectionanti-slip
- sheet on the floor
- door with air spring
- pallet fork pockets with safety locking pin
- protective bar mesh
- tool box

CE

INDEX	WIDTH	WEIGHT
CWP130	130 cm	259 kg
CWP240	240 cm	463 kg

FORKLIFT WORK PLATFORM ELEVATED VERSION

CWPP



SPECIFICATION

- CWPP – elevated version, increasing working rangeanti-slip
- sheet on the floor
- door with air spring
- pallet fork pockets with safety locking pin
- protective bar mesh

INDEX	WIDTH	WEIGHT
CWPP130	130 cm	331 kg

BUCKETS

BUCKET NANO

NSB



≠ 4 mm | ≠ 4 mm | 0,20 - 0,26 m³

SPECIFICATION

- 110x12 HB500 cutting edges
- reinforced cutting edges

INDEX	WIDTH	WEIGHT	VOL.
NSB120	120 cm	94 kg	0,20 m³
NSB140	140 cm	101 kg	0,23 m³
NSB160	160 cm	107 kg	0,26 m³

BUCKET MICRO

ASB



≠ 5 mm | ≠ 4 mm | 0,20 - 0,24 m³

SPECIFICATION

- 110x12 HB500 cutting edges
- reinforced cutting edges

INDEX	WIDTH	WEIGHT	VOL.
ASB110	110 cm	80 kg	0,20 m³
ASB120	120 cm	87 kg	0,22 m³
ASB130	130 cm	93 kg	0,24 m³

BUCKET MINI

SSB



SSBW





≠ 5 mm | ≠ 4 mm | 0,24 - 0,45 m³

SPECIFICATION

- 110x12 HB500 cutting edges
- reinforced cutting edges
- embossed side

OPTIONS

- SSBW – insert version
- SSB – ribbed version

INDEX	WIDTH	WEIGHT	VOL.
SSB090	90 cm	91 kg	0,24 m³
SSB100	100 cm	99 kg	0,26 m³
SSB110	110 cm	109 kg	0,29 m³
SSB120	120 cm	115 kg	0,32 m³
SSB140	140 cm	128 kg	0,37 m³
SSB150	150 cm	134 kg	0,39 m³
SSB160	160 cm	140 kg	0,42 m³
SSB180	180 cm	146 kg	0,45 m³

BUCKET MINI VOLUME

SVB



SVBW





≠ 5 mm | ≠ 5 mm | 0,32 - 0,71 m³

SPECIFICATION

- 110x12 HB500 cutting edge
- reinforced cutting edges
- embossed side

OPTIONS

- SVBW – insert version
- SVB – ribbed version

INDEX	WIDTH	WEIGHT	VOL.
SVB090	90 cm	135 kg	0,32 m³
SVB100	100 cm	142 kg	0,36 m³
SVB120	120 cm	157 kg	0,43 m³
SVB140	140 cm	172 kg	0,50 m³
SVB160	160 cm	187 kg	0,57 m³
SVB180	180 cm	206 kg	0,64 m³
SVB200	200 cm	227 kg	0,71 m³

BUCKET STANDARD

MSB





MSBW





≠ 5 mm | ≠ 4 mm | 0,36 - 0,72 m³

SPECIFICATION

- 110x12 HB500 cutting edge
- reinforced cutting edges
- embossed side

OPTIONS

- MSBW – insert version
- MSB – ribbed version

INDEX	WIDTH	WEIGHT	VOL.
MSB120	120 cm	121 kg	0,36 m³
MSB140	140 cm	128 kg	0,42 m³
MSB160	160 cm	140 kg	0,48 m³
MSB180	180 cm	153 kg	0,54 m³
MSB200	200 cm	169 kg	0,60 m³
MSB220	220 cm	186 kg	0,66 m³
MSB240	240 cm	226 kg	0,72 m³

BUCKET VOLUME

MVB



MVBW





≠ 5 mm | ≠ 5 mm | 0,40 - 0,80 m³

SPECIFICATION

- 110x16 HB500 cutting edge
- reinforced cutting edges
- embossed side

OPTIONS

- MVBW – insert version
- MVB – ribbed version

INDEX	WIDTH	WEIGHT	VOL.
MVB120	120 cm	147 kg	0,40 m³
MVB140	140 cm	168 kg	0,46 m³
MVB160	160 cm	189 kg	0,53 m³
MVB180	180 cm	210 kg	0,59 m³
MVB200	200 cm	230 kg	0,66 m³
MVB220	220 cm	244 kg	0,73 m³
MVB240	240 cm	259 kg	0,80 m³

BUCKET FOR STONE

MSBS





≠ 12 mm | Ø 30 mm | 0,29 - 0,50 m³

SPECIFICATION

- 72 mm bar spacing
- construction reinforced with thick material tubes
- profiled rake elements

INDEX	WIDTH	WEIGHT	VOL.
MSBS140	140 cm	230 kg	0,29 m³
MSBS160	160 cm	257 kg	0,34 m³
MSBS180	180 cm	284 kg	0,38 m³
MSBS200	200 cm	311 kg	0,42 m³
MSBS220	220 cm	338 kg	0,46 m³
MSBS240	240 cm	365 kg	0,50 m³

BUCKET FOR STONE WITH GRIPPER

MSBSG





≠ 12 mm | Ø 30 mm | 0,61 - 0,92 m³

SPECIFICATION

- 72 mm bar spacing
- construction reinforced with thick material tubes
- profiled rake elements

OPTIONS

- bolt on protection frame

INDEX	WIDTH	WEIGHT	VOL.
MSBSG160	160 cm	460 kg	0,61 m³
MSBSG200	200 cm	530 kg	0,77 m³
MSBSG240	240 cm	600 kg	0,92 m³

BUCKET FOR ROOT CROP MINI

SPB





SPBW





≠ 6 mm | Ø 20 mm | 0,26 - 0,48 m³

SPECIFICATION

- 50 mm bar spacing
- 150x20 HB500 cutting edge
- suitable for optional insert placement

OPTIONS

- SPBW – insert version

INDEX	WIDTH	WEIGHT	VOL.
SPB120	120 cm	161 kg	0,26 m³
SPB140	140 cm	189 kg	0,31 m³
SPB160	160 cm	214 kg	0,35 m³
SPB180	180 cm	240 kg	0,40 m³
SPB200	200 cm	267 kg	0,44 m³
SPB220	220 cm	292 kg	0,48 m³

BUCKET FOR ROOT CROP STANDARD

MPB







≠ 6 mm | Ø 16 mm | 0,57 - 0,98 m³

SPECIFICATION

- 30 mm bar spacing
- 150x20 HB500 cutting edge

INDEX	WIDTH	WEIGHT	VOL.
MPB140	140 cm	198 kg	0,57 m³
MPB160	160 cm	220 kg	0,66 m³
MPB180	180 cm	246 kg	0,74 m³
MPB200	200 cm	255 kg	0,82 m³
MPB220	220 cm	272 kg	0,90 m³
MPB240	240 cm	311 kg	0,98 m³

BUCKET FOR ROOT CROP MAXI

MBBP





MBBPW





≠ 6 mm | Ø 20 mm | 0,78 - 1,27 m³

SPECIFICATION

- 40 mm bar spacing
- 150x20 HB500 cutting edge

OPTIONS

- MBBPW – insert version

INDEX	WIDTH	WEIGHT	VOL.
MBBP160	160 cm	244 kg	0,78 m³
MBBP180	180 cm	271 kg	0,88 m³
MBBP200	200 cm	300 kg	0,98 m³
MBBP220	220 cm	327 kg	1,08 m³
MBBP240	240 cm	355 kg	1,18 m³
MBBP260	260 cm	380 kg	1,27 m³

BUCKET FOR ROOT CROP (POTATO)

AA





≠ 6 mm | ≠ 6 mm | 1,20 - 1,95 m³

SPECIFICATION

- Ø 60 mm reinforcing tubes
- 150x20 HB500 cutting edge
- designed to minimise damage to the material to be taken

INDEX	WIDTH	WEIGHT	VOL.
AA160	160 cm	414 kg	1,20 m³
AA180	180 cm	453 kg	1,35 m³
AA200	200 cm	486 kg	1,50 m³
AA220	220 cm	524 kg	1,65 m³
AA240	240 cm	560 kg	1,80 m³
AA260	260 cm	596 kg	1,95 m³

BUCKET FOR GRAIN

MSBP





≠ 6 mm	≠ 6 mm	0,57 - 0,98 m³

SPECIFICATION

- 150x16 HB500 cutting edge
- reinforcements on the sides

INDEX	WIDTH	WEIGHT	VOL.
MSBP140	140 cm	199 kg	0,57 m³
MSBP160	160 cm	224 kg	0,66 m³
MSBP180	180 cm	246 kg	0,74 m³
MSBP200	200 cm	267 kg	0,82 m³
MSBP220	220 cm	288 kg	0,90 m³
MSBP240	240 cm	309 kg	0,98 m³

STANDARD CONSTRUCTION BUCKET

SBC





≠ 6 mm	≠ 4 mm	0,26 - 0,45 m³

SPECIFICATION

- 150x16 HB500 cutting edge
- reinforced cutting edges

INDEX	WIDTH	WEIGHT	VOL.
SBC120	120 cm	124 kg	0,26 m³
SBC140	140 cm	145 kg	0,31 m³
SBC160	160 cm	165 kg	0,36 m³
SBC180	180 cm	186 kg	0,40 m³
SBC200	200 cm	207 kg	0,45 m³

BUCKET HEAVY DUTY MINI

XLHBS-A

≠ 6 mm | ≠ 5 mm | 0,71-1,22 m³



SPECIFICATION

- 150x16 HB500 cutting edge
- ribs ≠ 10 mm
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection

OPTIONS

- screwed-on tine L-184 - default spacing 285mm
- profiled sides increasing capacity
- bolt-on cutting edge HB500 150x16 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLHBSB-A
XLHBS-A140	140 cm	243 kg	0,71 m³	+ 0,14 m³
XLHBS-A160	160 cm	275 kg	0,82 m³	+ 0,16 m³
XLHBS-A180	180 cm	309 kg	0,92 m³	+ 0,18 m³
XLHBS-A200	200 cm	341 kg	1,02 m³	+ 0,2 m³
XLHBS-A220	220 cm	373 kg	1,12 m³	+ 0,22 m³
XLHBS-A240	240 cm	406 kg	1,22 m³	+ 0,24 m³

BUCKET HEAVY DUTY STANDARD

XLHBS-B

≠ 8 mm | ≠ 6 mm | 0,83-1,42 m³



SPECIFICATION

- 150x16 HB500 cutting edge
- ribs ≠ 10 mm
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection



OPTIONS

- screwed-on tine L-184 - default spacing 285mm
- profiled sides increasing capacity
- bolt-on cutting edge HB500 150x16 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLHBSB-B
XLHBS-B140	140 cm	317 kg	0,83 m³	+ 0,17 m³
XLHBS-B160	160 cm	356 kg	0,94 m³	+ 0,19 m³
XLHBS-B180	180 cm	391 kg	1,06 m³	+ 0,21 m³
XLHBS-B200	200 cm	429 kg	1,18 m³	+ 0,24 m³
XLHBS-B220	220 cm	468 kg	1,30 m³	+ 0,26 m³
XLHBS-B240	240 cm	508 kg	1,42 m³	+ 0,28 m³

BUCKET HEAVY DUTY VOLUME

XLHBS-C

≠ 8 mm | ≠ 6 mm | 1,31-2,13 m³



SPECIFICATION

- 200x20 HB500 cutting edge
- ribs ≠ 10 mm
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection

OPTIONS

- screwed-on tine L-250 - default spacing 285mm
- profiled sides increasing capacity
- bolt-on cutting edge HB500 200x20 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLHBSB-C
XLHBS-C160	160 cm	437 kg	1,31 m³	+ 0,26 m³
XLHBS-C180	180 cm	481 kg	1,48 m³	+ 0,3 m³
XLHBS-C200	200 cm	525 kg	1,64 m³	+ 0,33 m³
XLHBS-C220	220 cm	569 kg	1,80 m³	+ 0,36 m³
XLHBS-C240	240 cm	613 kg	1,97 m³	+ 0,39 m³
XLHBS-C260	260 cm	657 kg	2,13 m³	+ 0,43 m³

BUCKET HEAVY DUTY MAXI

XLHBS-D

≠ 8 mm | ≠ 6 mm | 1,62-2,63 m³



SPECIFICATION

- 200x20 HB500 cutting edge
- ribs ≠ 12 mm
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection

OPTIONS

- screwed-on tine L-250 - default spacing 285mm
- profiled sides increasing capacity
- bolt-on cutting edge HB500 200x20 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLHBSB-D
XLHBS-D160	160 cm	522 kg	1,62 m³	+ 0,32 m³
XLHBS-D180	180 cm	578 kg	1,82 m³	+ 0,36 m³
XLHBS-D200	200 cm	639 kg	2,02 m³	+ 0,4 m³
XLHBS-D220	220 cm	701 kg	2,22 m³	+ 0,44 m³
XLHBS-D240	240 cm	760 kg	2,42 m³	+ 0,48 m³
XLHBS-D260	260 cm	819 kg	2,63 m³	+ 0,53 m³

GENERAL PURPOSE LOADING BUCKET MINI

XLLBC-A



≠ 6 mm | ≠ 5 mm | 0,67-1,15 m³

SPECIFICATION

- 150x16 HB500 cutting edge
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection

OPTIONS

- profiled sides increasing capacity
- bolt-on cutting edge HB500 150x16 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLLBCB-A
XLLBC-A140	140 cm	239 kg	0,67 m³	+ 0,13 m³
XLLBC-A160	160 cm	257 kg	0,77 m³	+ 0,15 m³
XLLBC-A180	180 cm	306 kg	0,86 m³	+ 0,17 m³
XLLBC-A200	200 cm	340 kg	0,96 m³	+ 0,19 m³
XLLBC-A220	220 cm	380 kg	1,06 m³	+ 0,21 m³
XLLBC-A240	240 cm	412 kg	1,15 m³	+ 0,23 m³

GENERAL PURPOSE LOADING BUCKET STANDARD

XLLBC-B



≠ 6 mm | ≠ 5 mm | 0,84-1,44 m³

SPECIFICATION

- 150x20 HB500 cutting edge
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection

OPTIONS

- profiled sides increasing capacity
- bolt-on cutting edge HB500 150x20 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLLBCB-B
XLLBC-B140	140 cm	245 kg	0,84 m³	+ 0,17 m³
XLLBC-B160	160 cm	287 kg	0,96 m³	+ 0,19 m³
XLLBC-B180	180 cm	322 kg	1,08 m³	+ 0,22 m³
XLLBC-B200	200 cm	364 kg	1,20 m³	+ 0,24 m³
XLLBC-B220	220 cm	403 kg	1,32 m³	+ 0,26 m³
XLLBC-B240	240 cm	441 kg	1,44 m³	+ 0,29 m³

GENERAL PURPOSE LOADING BUCKET VOLUME

XLLBC-C



≠ 8 mm | ≠ 6 mm | 1,26-2,05 m³

SPECIFICATION

- 200x20 HB500 cutting edge
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection



OPTIONS

- profiled sides increasing capacity
- bolt-on cutting edge HB500 200x20 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLLBCB-C
XLLBC-C160	160 cm	416 kg	1,26 m³	+ 0,25 m³
XLLBC-C180	180 cm	467 kg	1,42 m³	+ 0,28 m³
XLLBC-C200	200 cm	515 kg	1,58 m³	+ 0,32 m³
XLLBC-C220	220 cm	561 kg	1,74 m³	+ 0,35 m³
XLLBC-C240	240 cm	608 kg	1,90 m³	+ 0,38 m³
XLLBC-C260	260 cm	655 kg	2,05 m³	+ 0,41 m³

GENERAL PURPOSE LOADING BUCKET MAXI

XLLBC-D



≠ 8 mm | ≠ 6 mm | 1,47-2,39 m³

SPECIFICATION

- 200x20 HB500 cutting edge
- reinforcements on the sides
- bottom reinforcements ≠ 10 mm
- reinforced side to bottom connection

OPTIONS

- profiled sides increasing capacity
- bolt-on cutting edge HB500 200x20 double-sided

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLLBCB-D
XLLBC-D160	160 cm	475 kg	1,47 m³	+ 0,29 m³
XLLBC-D180	180 cm	533 kg	1,66 m³	+ 0,33 m³
XLLBC-D200	200 cm	591 kg	1,84 m³	+ 0,37 m³
XLLBC-D220	220 cm	644 kg	2,02 m³	+ 0,4 m³
XLLBC-D240	240 cm	706 kg	2,21 m³	+ 0,44 m³
XLLBC-D260	260 cm	766 kg	2,39 m³	+ 0,48 m³

BUCKETS 4 IN 1

BUCKET 4 IN 1 MINI

S41BL

≠ 8 mm | ≠ 5 mm | 0,21-0,34 m³



SPECIFICATION

- cutting edge HB500 110x16 front grading
- cutting edge HB500 110x12 back grading
- reinforcements on the sides
- bottom reinforcements ≠4 mm

OPTIONS

- screwed-on tine L-184 - default spacing 285mm
- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
S41BL100	100 cm	176 kg	0,21 m³	4
S41BL110	110 cm	187 kg	0,23 m³	5
S41BL120	120 cm	198 kg	0,25 m³	5
S41BL140	140 cm	235 kg	0,29 m³	6
S41BL160	160 cm	253 kg	0,34 m³	7

BUCKET 4 IN 1 STANDARD

M41B

≠ 8 mm | ≠ 8 mm | 0,36-0,72 m³



SPECIFICATION

- cutting edge HB500 110x16 front grading
- cutting edge HB500 110x12 back grading
- reinforcements on the sides
- bottom reinforcements ≠ 6 mm
- additional reinforced construction above the width of 2 m

OPTIONS

- screwed-on tine L-184 from 2,0 m L-250 - default spacing 285mm
- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
M41B120	120 cm	293 kg	0,36 m³	5
M41B140	140 cm	318 kg	0,42 m³	5
M41B160	160 cm	342 kg	0,48 m³	6
M41B180	180 cm	364 kg	0,54 m³	7
M41B200	200 cm	387 kg	0,60 m³	7
M41B220	220 cm	479 kg	0,66 m³	8
M41B240	240 cm	509 kg	0,72 m³	8

BUCKET 4 IN 1 MAXI

XL41B

≠ 10 mm | ≠ 10 mm | 0,56-0,84 m³



SPECIFICATION

- cutting edge HB500 150x20 front grading
- cutting edge HB500 150x16 back grading
- reinforced cutting edges
- bottom reinforcements ≠ 8 mm

OPTIONS

- screwed-on tine L-250 - default spacing 285mm
- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XL41B160	160 cm	514 kg	0,56 m³	6
XL41B180	180 cm	542 kg	0,63 m³	6
XL41B200	200 cm	570 kg	0,70 m³	8
XL41B220	220 cm	598 kg	0,77 m³	8
XL41B240	240 cm	626 kg	0,84 m³	8

GENERAL INFORMATION

The 4in1 MAXI bucket is a universal attachment that combines four working functions in one solid tool: **digging, loading, pushing and grabbing**.Easy digging is ensured by the front cutting edge made of wear-resistant steel **HB500 150x20**.Loading and material handling are more efficient thanks to the optimized capacity of this model, ranging from **560 L to 840 L.**

After opening the jaw, pushing is performed by the reinforced bucket structure, equipped with a rear cutting edge made of wear-resistant steel **HB500 150x16**, enabling even material distribution and ground leveling.Secure gripping of various materials is ensured by serrated side edges, providing a firm and even grip.The model is designed for larger backhoe loaders.Two hydraulic cylinders ensure precise jaw opening, enabling efficient and safe operation.

GRADING BUCKET MINI

GB

≠ 8 mm | ≠ 5 mm | 0,35-0,50 m³



SPECIFICATION

- 150x16 HB500 cutting edge
- shell ≠ 5 mm
- bottom reinforcements ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.
GB140	140cm	155 kg	0,35 m³
GB160	160cm	175 kg	0,40 m³
GB180	180cm	195 kg	0,45 m³
GB200	200cm	215 kg	0,50 m³

GRADING BUCKET STANDARD

GD

≠ 8 mm | ≠ 8 mm | 0,97-1,05 m³



SPECIFICATION

- 200x20 HB500 cutting edge
- shell ≠ 6 mm
- bottom reinforcements ≠ 10 mm

INDEX	WIDTH	WEIGHT	VOL.
GD220	220cm	339 kg	0,97 m³
GD240	240cm	365 kg	1,05 m³

GRADING BUCKET MAXI

GE

≠ 10 mm | ≠ 10 mm | 1,69-1,78 m³



SPECIFICATION

- 300x30 HB500 cutting edge
- shell ≠ 8 mm
- bottom reinforcements ≠ 10 mm

INDEX	WIDTH	WEIGHT	VOL.
GE240	240cm	645 kg	1,69 m³
GE260	260cm	690 kg	1,78 m³

BUCKET FOR COBBLESTONE MINI

SPV



≠ 12 mm | Ø 20 mm | 0,31 - 0,41 m³



SPECIFICATION

- 44 mm bar spacing
- construction reinforced with thick material tubes
- profiled rake elements

INDEX	WIDTH	WEIGHT	VOL.
SPV140	140cm	162 kg	0,31 m³
SPV160	160cm	181 kg	0,36 m³
SPV180	180cm	202 kg	0,41 m³

BUCKET FOR COBBLESTONE STANDARD

MPV

≠ 12 mm | Ø 25 mm | 0,49 - 0,61 m³



SPECIFICATION

- 55 mm bar spacing
- construction reinforced with thick material tubes
- profiled rake elements

INDEX	WIDTH	WEIGHT	VOL.
MPV160	160cm	197 kg	0,49 m³
MPV180	180cm	221 kg	0,55 m³
MPV200	200cm	245 kg	0,61 m³

HIGH TIP BUCKET WITH GRAB

MHTBG

≠ 6 mm | ≠ 5 mm | 0,50 - 0,86 m³



SPECIFICATION

- 110x16 HB500 cutting edge
- easy access to greasing nipples
- tines made of forged steel
- 2 hydraulics section required

OPTIONS

- hydraulic solenoid divider (1 hydraulic section required)

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MHTBG140	140 cm	484 kg	0,50 m³	6
MHTBG160	160 cm	513 kg	0,58 m³	7
MHTBG180	180 cm	542 kg	0,65 m³	8
MHTBG200	200 cm	571 kg	0,72 m³	8
MHTBG220	220 cm	600 kg	0,79 m³	10
MHTBG240	240 cm	629 kg	0,86 m³	10

HIGH TIP BUCKET

MHTB

MHTBB

≠ 6 mm | ≠ 5 mm | 0,43 - 0,79 m³





SPECIFICATION

- 110x16 HB500 cutting edge
- easy access to greasing nipples
- large discharge angle

OPTIONS

- overcenter valve - VBCD
- profiled sides increasing capacity

INDEX	WIDTH	WEIGHT	VOL.	VOL. MHTBB
MHTB120	120 cm	351 kg	0,43 m³	+ 0,13 m³
MHTB140	140 cm	381 kg	0,50 m³	+ 0,17 m³
MHTB160	160 cm	411 kg	0,58 m³	+ 0,19 m³
MHTB180	180 cm	441 kg	0,65 m³	+ 0,22 m³
MHTB200	200 cm	471 kg	0,72 m³	+ 0,26 m³
MHTB220	220 cm	501 kg	0,79 m³	+ 0,29 m³

HIGH TIP BUCKET VOLUME

MHTBM

MHTBMB

≠ 8 mm | ≠ 5 mm | 0,96 - 1,92 m³





SPECIFICATION

- 150x16 HB500 cutting edge
- easy access to greasing nipples

OPTIONS

- overcenter valve - VBCD
- profiled sides increasing capacity

INDEX	WIDTH	WEIGHT	VOL.	VOL. MHTBMB
MHTBM140	140 cm	604 kg	0,96 m³	+ 0,3 m³
MHTBM160	160 cm	640 kg	1,12 m³	+ 0,34 m³
MHTBM180	180 cm	680 kg	1,28 m³	+ 0,39 m³
MHTBM200	200 cm	725 kg	1,44 m³	+ 0,43 m³
MHTBM220	220 cm	759 kg	1,60 m³	+ 0,48 m³
MHTBM240	240 cm	793 kg	1,76 m³	+ 0,52 m³
MHTBM260	260 cm	827 kg	1,92 m³	+ 0,56 m³

HIGH TIP BUCKET MAXI

XLHTB

XLHTBB

≠ 8 mm | ≠ 6 mm | 1,61 - 2,76 m³





SPECIFICATION

- 200x20 HB500 cutting edge
- easy access to greasing nipples
- overcenter valve - VBCD as a standard

OPTIONS

- profiled sides increasing capacity

INDEX	WIDTH	WEIGHT	VOL.	VOL. XLHTBB
XLHTB160	160 cm	846 kg	1,61 m³	+ 0,44 m³
XLHTB180	180 cm	912 kg	1,84 m³	+ 0,5 m³
XLHTB200	200 cm	978 kg	2,07 m³	+ 0,55 m³
XLHTB220	220 cm	1044 kg	2,30 m³	+ 0,62 m³
XLHTB240	240 cm	1110 kg	2,53 m³	+ 0,66 m³
XLHTB260	260 cm	1176 kg	2,76 m³	+ 0,72 m³

BUCKET WITH GRAB MICRO

ABWG



≠ 8 mm | ≠ 4 mm | 0,21-0,34 m³

SPECIFICATION

- screwed-on side ≠ 6 mm
- 110x12 HB500 cutting edge
- solid steel grab tines ≠ 12 mm - L: 300 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
ABWG100	100 cm	130 kg	0,21 m³	4
ABWG120	120 cm	138 kg	0,25 m³	5
ABWG140	140 cm	149 kg	0,29 m³	5
ABWG160	160 cm	160 kg	0,34 m³	6

BUCKET WITH GRAB MINI

SBWG



≠ 10 mm | ≠ 5 mm | 0,32-0,54 m³

SPECIFICATION

- high quality forged tines - L: 585 mm
- screwed-on side ≠ 5 mm
- 2 screwed-on side tines
- 110x12 HB500 cutting edge
- 2 cylinders above the width of 1,2 m

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
SBWG90	90 cm	164 kg	0,32 m³	4
SBWG110	110 cm	186 kg	0,40 m³	5
SBWG120	120 cm	198 kg	0,43 m³	6
SBWG140	140 cm	228 kg	0,50 m³	7
SBWG150	150 cm	236 kg	0,54 m³	7

BUCKET WITH GRAB STANDARD

MBWG





≠ 10 mm | ≠ 5 mm | 0,77-1,32 m³

SPECIFICATION

- high quality forged tines - L: 660 mm
- screwed-on side ≠ 6 mm
- 2 screwed-on side tines
- 110x16 HB500 cutting edge
- the widths above of 2 m – 3 hinges

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MBWG140	140 cm	294 kg	0,77 m³	6
MBWG160	160 cm	318 kg	0,88 m³	7
MBWG180	180 cm	342 kg	0,99 m³	8
MBWG200	200 cm	369 kg	1,10 m³	8
MBWG220	220 cm	403 kg	1,21 m³	10
MBWG240	240 cm	430 kg	1,32 m³	10

BUCKET WITH GRAB MAXI

XLBWG





≠ 12 mm | ≠ 6 mm | 1,30-1,87 m³

SPECIFICATION

- high quality forged tines - L: 770 mm
- screwed-on side ≠ 8 mm
- 2 screwed-on side tines
- 150x20 HB500 cutting edge
- split jaw the width above 2,0 m

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLBWG180	180 cm	515 kg	1,30 m³	8
XLBWG200	200 cm	541 kg	1,44 m³	10
XLBWG220	220 cm	588 kg	1,58 m³	10
XLBWG240	240 cm	632 kg	1,73 m³	11
XLBWG260	260 cm	680 kg	1,87 m³	12

BUCKET WITH GRAB SUITED TO LOADER KINEMATICS

BUCKET WITH GRAB FOR LOW DENSITY MATERIALS

BUCKET WITH GRAB FOR RECYCLING

BUCKET FOR SILAGE MINI

SBGB

≠ 6 mm | ≠ 4 mm | 0,27-0,48 m³



SPECIFICATION

- 110x12 HB500 cutting edge
- 2 screwed-on tines in the grab
- grab tines ≠ 10 mm
- bolted sides ≠ 4 mm

OPTIONS

- pressure relief valve - VMP
- bolt-on cutting edge

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
SBGB090	90 cm	182 kg	0,27 m³	3
SBGB100	100 cm	190 kg	0,30 m³	3
SBGB110	110 cm	197 kg	0,33 m³	4
SBGB130	130 cm	209 kg	0,39 m³	4
SBGB140	140 cm	214 kg	0,42 m³	4
SBGB150	150 cm	218 kg	0,45 m³	5
SBGB160	160 cm	226 kg	0,48 m³	6

BUCKET FOR SILAGE STANDARD

MBGB

≠ 10 mm | ≠ 5 mm | 0,42-0,92 m³



SPECIFICATION

- 110x16 HB500 cutting edge
- 2 screwed-on tines in the grab
- grab tines ≠ 16 mm above the width of 1,4 m
- bolted sides ≠ 5 mm

OPTIONS

- pressure relief valve - VMP
- bolt-on cutting edge

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MBGB100	100 cm	273 kg	0,42 m³	4
MBGB120	120 cm	306 kg	0,50 m³	4
MBGB140	140 cm	325 kg	0,59 m³	4
MBGB160	160 cm	374 kg	0,67 m³	5
MBGB180	180 cm	425 kg	0,76 m³	6
MBGB200	200 cm	439 kg	0,84 m³	6
MBGB220	220 cm	480 kg	0,92 m³	7

FEEDING

PRO Line

BUCKET FOR SILAGE MAXI

MBGBM

YouTube



≠ 8 mm | ≠ 6 mm | 0,95-1,38 m³

SPECIFICATION

- 150x20 HB500 cutting edge
- 2 screwed-on tines in the grab
- grab tines ≠ 18 mm
- bolted sides ≠ 6 mm
- width above 2,2 m - 3 hinge

OPTIONS

- pressure relief valve - VMP
- bolt-on cutting edge

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MBGBM180	180 cm	675 kg	0,95 m³	6
MBGBM200	200 cm	708 kg	1,06 m³	6
MBGBM220	220 cm	758 kg	1,17 m³	7
MBGBM240	240 cm	781 kg	1,27 m³	7
MBGBM260	260 cm	822 kg	1,38 m³	7

BUCKET FOR SILAGE MAXI TELESCOPIC

XLBGB





≠ 12 mm | ≠ 6 mm | 1,42-2,05 m³

SPECIFICATION

- 200x20 HB500 cutting edge
- 2 screwed-on tines in the grab
- grab tines ≠ 18 mm
- bolted sides ≠ 10 mm

OPTIONS

- pressure relief valve - VMP
- bolt-on cutting edge

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLBGB180	180 cm	807 kg	1,42 m³	6
XLBGB200	200 cm	855 kg	1,58 m³	7
XLBGB220	220 cm	920 kg	1,74 m³	7
XLBGB240	240 cm	954 kg	1,90 m³	8
XLBGB260	260 cm	1001 kg	2,05 m³	9

BUCKET FOR SILAGE GOLIAT

XLBGBM





≠ 12 mm | ≠ 6 mm | 2,14-2,78 m³

SPECIFICATION

- 200x20 HB500 cutting edge
- 2 screwed-on tines in the grab
- grab tines ≠ 18 mm
- bolted sides ≠ 10 mm

OPTIONS

- pressure relief valve - VMP
- bolt-on cutting edge

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLBGBM200	200 cm	1041 kg	2,14 m³	6
XLBGBM220	220 cm	1079 kg	2,35 m³	6
XLBGBM240	240 cm	1100 kg	2,57 m³	7
XLBGBM260	260 cm	1116 kg	2,78 m³	8

BUCKET WITH GRAB HEAVY DUTY FOR RECYCLING

XLBGB-G



≠ 12 mm | ≠ 6 mm | 1,42-2,05 m³

SPECIFICATION

- full sides
- tube at the end of the grab
- bolt-on blade

OPTIONS

- pressure relief valve - VMP

INDEX	WIDTH	WEIGHT	VOL.
XLBGB180-G	180 cm	848 kg	1,42 m³
XLBGB200-G	200 cm	902 kg	1,58 m³
XLBGB220-G	220 cm	968 kg	1,74 m³
XLBGB240-G	240 cm	1002 kg	1,90 m³
XLBGB260-G	260 cm	1056 kg	2,05 m³

SILAGE CUTTER WITH FORKS AND SILAGE CUTTER WITH BUCKET

GENERAL INFORMATION

YouTube

Silage cutters are used for precise cutting feed from the heaps, cutting bales and handling feed to a desired location.

We divide them into SILAGE CUTTER WITH FORKS, SILAGE CUTTER WITH BUCKET and MULTI CUTTER. Cutting teeth can be welded or bolted.

SILAGE CUTTER WITH FORKS performs very well with grass silage, because the forks can easily be pierced into the heap. This allows full use of the machine capacity and reduces the number of journeys during feed preparation.

SILAGE CUTTER WITH BUCKET is better suited for loose feed such as maize. The bucket allows cleaning up leftovers and moving material around the working area.

MULTI CUTTER is an optimal combination of both types, with an additional option of cutting bales directly into the mixing wagon, as it can hold the foil.

Silage cutters in general are a better solution for withdrawing silage from heaps compared to traditional fork grabs and bucket grabs, as they ensure better hygiene during feed collection.

Efficiency table of collecting feed

SYMBOL	MATERIAL	MSC	XLSC	MSCB	XLCB	MSSCM
SD	Sawdust	●	●	●	●	●
MS	Separated manure	●	●	●	●	●
SM	Maize silage	●	●	●	●	●
GS	Chopped grass silage (max. 6 cm)	●	●	●	●	●
TMR	TMR	●	●	●	●	●
B	Silage bales	●	●	●	●	●

SILAGE CUTTER MULTI 3 IN 1

MSSCM

≠ 8 mm | 0,83 m³ | 180bar - 25L/min



SPECIFICATION

- bale cutting
- silage cutting from the heap
- bulk bucket
- screwed-on cutting teeth of tool steel
- hooks for holding the foil
- sides ≠ 8 mm with cutting edge

OPTIONS

- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.
MSSCM160	160 cm	702 kg	0,83 m³

SILAGE CUTTER WITH FORKS

MSC



180bar - 25L/min

0,65-1,00 m³

≠ 8 mm



SPECIFICATION

- high quality forged tines
- cutting teeth made of quality steel
- grid for better visibility
- sides ≠8 mm with cutting edge

OPTIONS

- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
MSC110	110 cm	390 kg	0,65 m³	8
MSC130	130 cm	424 kg	0,77 m³	9
MSC150	150 cm	453 kg	0,89 m³	10
MSC170	170 cm	485 kg	1,00 m³	12

SILAGE CUTTER WITH FORKS BOLT-ON TEETH

XLSC

180bar - 25L/min

0,65-0,85 m³

≠ 8 mm



SPECIFICATION

- high quality forged tines
- cutting teeth made of tool steel
- sides ≠ 8 mm with cutting edge
- grid for better visibility

OPTIONS

- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLSC120	120 cm	433 kg	0,65 m³	9
XLSC140	140 cm	471 kg	0,75 m³	10
XLSC160	160 cm	504 kg	0,85 m³	12

SILAGE CUTTER WITH BUCKET

MSCB

YouTube



180bar - 25L/min

0,66-0,87 m³

≠ 8 mm



SPECIFICATION

- cutting teeth made of quality steel
- sides ≠ 8 mm with cutting edge
- 110x16 HB500 cutting edge

OPTIONS

- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.
MSCB130	130 cm	542 kg	0,66 m³
MSCB150	150 cm	573 kg	0,77 m³
MSCB170	170 cm	601 kg	0,87 m³

SILAGE CUTTER WITH BUCKET BOLT-ON TEETH

XLCB



180bar - 25L/min

0,65-0,87 m³

≠ 8 mm



SPECIFICATION

- cutting teeth made of quality steel
- sides ≠ 8 mm with cutting edge
- 110x16 HB500 cutting edge

OPTIONS

- flow divider valve - DFL

INDEX	WIDTH	WEIGHT	VOL.
XLCB120	120 cm	485 kg	0,65 m³
XLCB140	140 cm	566 kg	0,76 m³
XLCB160	160 cm	647 kg	0,87 m³

SILAGE CUTTER WITH FORKS AND SILAGE CUTTER WITH BUCKET MAXI POWER

GENERAL INFORMATION

MAXI POWER series cutters are designed to ensure maximum cutting force. As standard, they are equipped with three hydraulic cylinders. This guarantees uncompromising cutting performance without stopping the cutting edge, even in very compacted and fibrous silage clamps.

When using this type of cutter, the risk of tearing the silage structure and unnecessary aeration is minimized.

The cutting teeth are made of wear-resistant tool steel and are replaceable, making servicing of the cutting unit easier. In case of damage, individual teeth can be quickly replaced, which significantly reduces downtime.

The entire cutter structure is based on a reinforced frame with a grid for better visibility, allowing full control over the cutting process while maintaining tightness for safe feed transport.

SILAGE CUTTER WITH FORKS MAXI POWER

XLSC



180bar - 35L/min

1,02-1,17 m³

≠ 8 mm





SPECIFICATION

- high quality forged tines
- cutting teeth made of tool steel
- sides ≠ 8 mm with cutting edge
- grid for better visibility
- 3 hydraulic cylinders

PRO Line

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
XLSC180	180 cm	609 kg	1,02 m³	13
XLSC205	205 cm	666 kg	1,06 m³	15
XLSC225	225 cm	733 kg	1,17 m³	17

SILAGE CUTTER WITH BUCKET MAXI POWER

XLCB



180bar - 35L/min

1,01-1,11 m³

≠ 8 mm





SPECIFICATION

- cutting teeth made of tool steel
- sides ≠ 8 mm with cutting edge
- 3 hydraulic cylinders

INDEX	WIDTH	WEIGHT	VOL.
XLCB205	205 cm	715 kg	1,01 m³
XLCB225	225 cm	752 kg	1,11 m³

BUCKETS WITH FEEDING AUGER



GENERAL INFORMATION

Feeding buckets can serve as distribution of loose, chopped and preferably dry feed. Load can be discharged on either side, left or right.

Depending on the model of device, feed can be loaded with different methods, just simply driving into loose feed to pick it up, scraped from the heap using a built-in grab, or milled from the silage face with a silage defacer, which is undoubtedly the best solution as it leaves a smooth surface of the clamp, preventing air from penetrating deeper into the silage.

The standard discharge spout allows for precise unloading of feed into the feeding wagon or other containers.

Feeding buckets are very versatile attachments that help save time and reduce labor effort.

As standard, the buckets are equipped with agitators. However, when working with materials characterized by low resistance (such as sand or lime), the use of agitators is not recommended, as they generate unnecessary resistance. Their primary function is to prevent bridging of materials (e.g. maize silage), which may accumulate in the upper part of the bucket.

The side flaps open and close depending on the direction of oil flow.

Efficiency table of collecting feed

SYMBOL	MATERIAL	FBSS FBSV	FBWGS FBWGV	FBHSS FBHSV
SD	Sawdust	●	●	●
CS	Chopped straw with husk chaff (max. 1,3cm)	●	●	●
RS	Chopped straw	●	●	●
MS	Separated manure	●	●	●
CA	Lime	●	●	●
BS	Dry sand	●	●	●
LSW	Straw, lime, water mix (1:5:2)	●	●	●
SP	Straw pellets (max. 2 cm)	●	●	●
SM	Maize silage	●	●	●
GS	Chopped grass silage (max. 6 cm)	●	●	●
CR	Whole grains (wheat, barley, corn, etc.)	●	●	●
TMR	TMR	●	●	●

BOLTED KNIVES ON DEFACER



Collected feed is additionally chopped, easier to replace broken parts. It is advised to use these knives with high density heaps.

ADDITIONAL MOTOR IN AUGER

It brings more power to the auger so it can handle difficult more humid materials. In certain width range those additional motors are already installed as standard, due to that is required for operating efficiency.

ADDITIONAL AGITATORS



Main task of agitators is to loosen up light material, because they are likely to get hang in the upper area of the bucket, in basic setup there are 2 agitators

BUCKET WITH FEEDING AUGER

FBSS





≠ 6 mm | ≠ 5 mm | 0,85-1,70 m³ | 180bar - 45L/min

SPECIFICATION

- possibility of feed distribution on both sides
- agitators to prevent the feed suspension
- 150x16 HB500 cutting edge
- 2 hydraulic motors from the width of 1,8 m
- recommended flow rate 45 l/min

OPTIONS

- pressure relief valve - VMP
- additional motor
- additional agitator

INDEX	WIDTH	WEIGHT	VOL.
FBSS120	120 cm	441 kg	0,85 m³
FBSS140	140 cm	471 kg	0,99 m³
FBSS160	160 cm	503 kg	1,14 m³
FBSS180	180 cm	529 kg	1,28 m³
FBSS200	200 cm	560 kg	1,42 m³
FBSS220	220 cm	594 kg	1,56 m³
FBSS240	240 cm	622 kg	1,70 m³

BUCKET WITH FEEDING AUGER VOLUME

FBSV





≠ 6 mm | ≠ 5 mm | 1,09-2,18 m³ | 180bar - 45L/min

SPECIFICATION

- possibility of feed distribution on both sides
- agitators to prevent the feed suspension
- 150x16 HB500 cutting edge
- 2 hydraulic motors from the width of 1,6 m
- recommended flow rate 45 l/min

OPTIONS

- pressure relief valve - VMP
- additional motor
- additional agitator

INDEX	WIDTH	WEIGHT	VOL.
FBSV120	120 cm	475 kg	1,09 m³
FBSV140	140 cm	519 kg	1,27 m³
FBSV160	160 cm	568 kg	1,46 m³
FBSV180	180 cm	614 kg	1,64 m³
FBSV200	200 cm	655 kg	1,82 m³
FBSV220	220 cm	701 kg	2,00 m³
FBSV240	240 cm	745 kg	2,18 m³

BUCKET WITH FEEDING AUGER AND GRAB

GENERAL INFORMATION

Feeding buckets equipped with a grab allow the operator to first collect the required amount of feed from the silage clamp and then load it efficiently using the bucket.

The grab cylinders are powered via an electrohydraulic valve, which means that no additional hydraulic section is required.

During transport to the feeding table, the grab secures the material against spillage, minimizing feed losses.

BUCKET WITH FEEDING AUGER AND GRAB

FBWGS

≠ 6 mm | ≠ 5 mm | 1,14-1,56 m³ | 180bar - 45L/min



SPECIFICATION

- feed collection grab
- only 1 hydraulic section required
- 150x16 HB500 cutting edge
- 2 hydraulic motors from the width of 1,8 m
- recommended flow rate 45 l/min

OPTIONS

- pressure relief valve - VMP
- additional motor
- additional agitator

INDEX	WIDTH	WEIGHT	VOL.
FBWGS160	160 cm	635 kg	1,14 m³
FBWGS180	180 cm	698 kg	1,28 m³
FBWGS200	200 cm	765 kg	1,42 m³
FBWGS220	220 cm	819 kg	1,56 m³

BUCKET WITH FEEDING AUGER AND GRAB VOLUME

FBWGV

≠ 6 mm | ≠ 5 mm | 1,46-2,00 m³ | 180bar - 45L/min



SPECIFICATION

- feed collection grab
- only 1 hydraulic section required
- 150x16 HB500 cutting edge
- 2 hydraulic motors from the width of 1,6 m
- recommended flow rate 45 l/min

OPTIONS

- pressure relief valve - VMP
- additional motor
- additional agitator

INDEX	WIDTH	WEIGHT	VOL.
FBWGV160	160 cm	715 kg	1,46 m³
FBWGV180	180 cm	780 kg	1,64 m³
FBWGV200	200 cm	845 kg	1,82 m³
FBWGV220	220 cm	910 kg	2,00 m³

BUCKET WITH SILAGE DEFACER

FEEDING

PRO Line

BUCKET WITH SILAGE DEFACER

FBHSS



≠ 6 mm | ≠ 5 mm | 1,14-1,56 m³ | 180bar - 50L/min

SPECIFICATION

- hydraulic defacer for feed collection
- only 1 hydraulic section required
- 150x16 HB500 cutting edge
- 2 hydraulic motors in auger from the width of 1,8 m
- recommended flow rate 50 l/min

OPTIONS

- bolted blades on the shaft
- pressure relief valve - VMP
- additional motor
- additional agitator

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
FBHSS160	160 cm	630 kg	1,14 m³	46
FBHSS180	180 cm	720 kg	1,28 m³	53
FBHSS200	200 cm	814 kg	1,42 m³	60
FBHSS220	220 cm	920 kg	1,56 m³	66

BUCKET WITH SILAGE DEFACER VOLUME

FBHSV





≠ 6 mm | ≠ 5 mm | 1,46-2,00 m³ | 180bar - 50L/min

SPECIFICATION

- hydraulic defacer for feed collection
- only 1 hydraulic section required
- 150x16 HB500 cutting edge
- 2 hydraulic motors in auger from the width of 1,6 m
- recommended flow rate 50 l/min

OPTIONS

- bolted blades on the shaft
- pressure relief valve - VMP
- additional motor
- additional agitator

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TINES
FBHSV160	160 cm	760 kg	1,46 m³	46
FBHSV180	180 cm	825 kg	1,64 m³	53
FBHSV200	200 cm	917 kg	1,82 m³	60
FBHSV220	220 cm	1020 kg	2,00 m³	66

BUCKET WITH SILAGE DEFACER FBHSS-J FBHSV-V

FBHSS-J



≠ 6 mm | ≠ 5 mm | 1,14-1,56 m³ | 180bar - 50L/min

SPECIFICATION

- hydraulic defacer for feed collection
- only 1 hydraulic section required
- 150x16 HB500 cutting edge
- recommended flow rate 50 l/min

INDEX	WIDTH	WEIGHT	VOL.	INDEX	WIDTH	WEIGHT	NO. OF TINES
FBHSS160-J	160 cm	520 kg	1,14 m³	FBHSV160-V	552 kg	1,46 m³	44
FBHSS180-J	180 cm	570 kg	1,28 m³	FBHSV180-V	606 kg	1,64 m³	53
FBHSS200-J	200 cm	613 kg	1,42 m³	FBHSV200-V	653 kg	1,82 m³	60
FBHSS220-J	220 cm	654 kg	1,56 m³	FBHSV220-V	698 kg	2,00 m³	66

BUCKETS FOR BEDDING

GENERAL INFORMATION

Bedding buckets are used to distribute bedding material over the animal bed area. Distribution can be held either on left or right side. Bedding material is simply picked up with the bucket.

Depending on the model, they are equipped with working shafts inside the bucket that tear the straw or any other material and allow it to drop onto the conveyor belt, which throws it in the desired direction.

The working shafts can be reconfigured depending on the user's needs, in order to maximize the performance of the machine. There are also solutions available for extremely loose materials such as pellets, which require very precise dosing on the belt.

As standard, the equipment is fitted with cutting knives on the upper shafts and collecting knives on the lower shaft. A hydraulic sliding gate can be applied in all models of the equipment.

The spreading range depends strongly on the type of material. Heavier and more compact materials are thrown further – for example separated manure can reach realistically up to approx. 4 meters. Lightweight and less cohesive materials such as straw or sawdust typically reach a distance of approx. 2 meters.

Efficiency table of collecting feed

SYMBOL	MATERIAL	BBMI	BBUN	BBHV	BBHV3S	BBUNF
SD	Sawdust	●	●	●	●	●
CS	Chopped straw with husk chaff (max. 1,3cm)	●	●	●	●	●
RS	Chopped straw	●	●	●	●	●
MS	Separated manure	●	●	●	●	●
CA	Lime	●	●	●	●	●
BS	Dry sand	●	●	●	●	●
LSW	Straw, lime, water mix (1:5:2)	●	●	●	●	●
SP	Straw pellets (max. 2 cm)	●	●	●	●	●
SM	Maize silage	●	●	●	●	●
GS	Chopped grass silage (max. 6 cm)	●	●	●	●	●
CR	Whole grains (wheat, barley, corn, etc.)	●	●	●	●	●
TMR	TMR	●	●	●	●	●

BUCKET FOR BEDDING MINI

BBMI

1,04-1,35 m³

180bar - 55L/min



SPECIFICATION

- bedding with chopped straw, sawdust and other lightweight materials
- shaft and belt speed control
- bedding distribution on both sides
- shell ≠ 4 mm
- 110x12 mm HB500 cutting edge
- effective range approx. 4 m
- 2 hydraulic motors
- polyamide rollers
- recommended flow rate 55 L/min

INDEX	WIDTH	WEIGHT	VOL.
BBMI120	120 cm	388 kg	1,04 m³
BBMI155	155 cm	465 kg	1,35 m³

BUCKET FOR BEDDING UNIVERSAL

BBUN

YouTube

1,33-2,15 m³

180bar - 55L/min



SPECIFICATION

- bedding with chopped straw, sawdust and other lightweight materials
- shaft and belt speed control
- bedding distribution on both sides
- shell ≠ 4 mm
- 110x12 mm HB500 cutting edge
- effective range approx. 4 m
- 2 hydraulic motors
- polyamide rollers
- recommended flow rate 55 L/min

INDEX	WIDTH	WEIGHT	VOL.
BBUN120	120 cm	398 kg	1,33 m³
BBUN155	155 cm	476 kg	1,72 m³
BBUN180	180 cm	553 kg	2,00 m³
BBUN220	220 cm	640 kg	2,15 m³

PRO Line

FEEDING

BUCKET FOR BEDDING MAXI

BBHV

2,63 m³

180bar - 55L/min



SPECIFICATION

- bedding with chopped straw, sawdust and other lightweight materials
- shaft and belt speed control
- bedding distribution on both sides
- shell ≠ 5 mm
- 110x12 mm HB500 cutting edge
- effective range approx. 4 m
- 2 hydraulic motors
- polyamide rollers
- recommended flow rate 55 l/min

INDEX	WIDTH	WEIGHT	VOL.
BBHV180	180 cm	698 kg	2,63 m³

BUCKET FOR BEDDING MAXI POWER

BBHV3S

2,63 m³

180bar - 70L/min



SPECIFICATION

- bedding with chopped straw, sawdust and other lightweight materials
- shaft and belt speed control
- bedding distribution on both sides
- shell ≠ 5 mm
- 110x12 mm HB500 cutting edge
- effective range approx. 4 m
- 3 hydraulic motors
- polyamide rollers
- recommended flow rate 70 L/min

INDEX	WIDTH	WEIGHT	VOL.
BBHV3S180	180 cm	760 kg	2,63 m³

BUCKET FOR BEDDING WITH HYDRAULIC CHUTE OPENING DISCHARGE

BBUN180F

2,00 m³

180bar - 55L/min



SPECIFICATION

- bedding with chopped straw, sawdust and other lightweight materials
- shaft and belt speed control
- bedding distribution on both sides
- shell ≠ 4 mm
- 110x12 mm HB500 cutting edge
- effective range approx. 4 m
- 2 hydraulic motors
- polyamide rollers
- hydraulic chute opening discharge with indicator
- recommended flow rate 55 l/min

INDEX	WIDTH	WEIGHT	VOL.
BBUN180F	180 cm	565 kg	2,00 m³

ADDITIONAL ACCESSORIES

HYDRAULIC CHUTE OPENING DISCHARGE WITH INDICATOR

- precisely regulates the amount of dosed material

DISTRIUBUTION /FUNNEL REDUCER



- DISTRIUBUTION REDUCER: reduce the throw range
- FUNNEL REDUCER: helps to reduce amount of spilled materials, recommended to very loose materials

EXTENSION

- extension adding volume

DIFFERENT TYPE OF BLADES

- different type of blades allows to work with different materials



BALE UNROLLER



BASIC VERSION

VERSION WITH 1-ROTOR FOR BEDDING



VERSION WITH 2-ROTORS FOR BEDDING

GENERAL INFORMATION

Bale unrollers are mainly designed to unroll bales straight onto cattle feed table, which saves time and reduces feed losses. They can also be used to add unrolled bale straight into mixing vagon, which speeds up the whole process of preparing TMR and consumes less energy. In extended version with optional spreading shaft we gain an ability to do the bedding as well, that makes this product very versatile. With ease unroller works with bales up to 180cm. This device has an built in transport frame, so there is no need to switch tools while bringing bales from the shed to a place where we are currently working. After the bale is loaded on the unroller bed, operator slides spikes in dedicated spots in the frame and lifts with a bit of tilting towards the loader a simple mechanisim of AUTOLOCK attaches both parts to guarante safety while the whole process. Afterwards the foil and net has to be removed manually and the unrolling can begin.

Disconnecting hydraulic hoses in BPBR happens automatically while driving backwards with the machines settled on the ground, so there is no risk of damaging it, to connect it back together the opeartor has to do it manually.

Galvanized chain extends the lifespan of efficient functioning of the machine. The unroller bed is sealed with light polyamide material which further prevents loss of feed.

ELECTRIC VERSION 1,5 kW

Efficiency table of collecting feed

SYMBOL	MATERIAL	BPBU	BPBR	BUE
HB	Silage bales	●	●	●
OB	Oat bales	●	●	●
SB	Straw bales	●	●	●
GB	Lucerne bales	●	●	●
CA	Hay bales	●	●	●

SIDE DEFLACTOR

Helps to distribute the feed more to the side available declactor of different lengths 200mm - 400mm

SAFETY BAR

Bale safety bar

SUPPORT LEGS

Various height of support legs

BEDDING ROTOR

This is a optional feature that can be mounted on a basic machine frame. Material that get into the spreading rotor is thrown about 4m away, which is just enough to nicely cover free stand barn cattle beds. Rotor spikes are galvanized and have a safety lock on the nuts so they do not get loose while intensive use.

FEEDING

BALE UNROLLER

BPBU

180bar - 25L/min

485 kg



SPECIFICATION

- silage bale feeding
- straw bale spreading
- unrolling speed control
- bedding distribution on both sides
- galvanized chain
- AUTOLOCK system
- chain secured in the guide channel
- maximum bale weight 1000 kg

BALE UNROLLER WITH ROTOR FOR BEDDING

BPBR

YouTube

180bar - 55L/min

550 kg



SPECIFICATION

- rotor for bedding
- Silage bale feeding
- straw bale spreading
- spreading speed control
- bedding distribution on both sides
- galvanized chain
- AUTOLOCK system
- chain secured in the guide channel
- recommended flow rate 55 L/min
- maximum bale weight 1000 kg

OPTIONS

- rotor can be set either on left or right side

ELECTRIC BALE UNROLLER BASIC

BUE

1,5 kW

520 kg



SPECIFICATION

- Silage bale feeding
- straw bale spreading
- bedding distribution on both sides
- galvanized chain
- power supply voltage 400V
- electric motor with reduction gearbox 1,5 kW
- constant speed
- pallet fork pockets
- maximum bale weight 1000 kg

OPTIONS

- safety bar
- various height of support legs

PRO Line

ELECTRIC BALE UNROLLER PLUS

BUE-F

3 kW

590 kg



SPECIFICATION

- Silage bale feeding
- straw bale spreading
- bedding distribution on both sides
- galvanized chain
- power supply voltage 400V
- electric motor with reduction gearbox 3kW
- adjustable speed
- pallet fork pockets
- safety bar
- maximum bale weight 1000 kg

OPTIONS

- various height of support legs

GENERAL INFORMATION

The Electric Bale Unroller PLUS BUE-F is designed for unrolling straw bales in farms where repeatability of operation and the ability to work independently of a tractor are essential. The electric drive system ensures a constant operating speed, enabling even bedding distribution without tearing the material.

The use of an electric motor with a reduction gearbox allows direct transfer of torque to the working unit, minimizing energy losses and reducing mechanical overload. This solution is particularly effective for continuous operation and in livestock buildings, where low noise levels and the absence of exhaust emissions are important.

The frame structure and bale stabilizing elements limit bale movement during operation, which is especially important when handling large-diameter bales with varying density. The ability to work on both sides, along with optional support legs with adjustable height, allows the machine to be adapted to different layouts of corridors and working areas, reducing straw losses and improving work ergonomics.

BALE CUTTER

GENERAL INFORMATION

The MBC bale cutter is primarily designed for cutting silage and straw bales. It can also be used for handling bales and transporting them to feeding areas or for loading into mixing wagons, with hooks for holding the foil or net.

Cutting bales directly into the mixing wagon provides measurable benefits, including shorter mixing time and reduced energy consumption required for feed preparation.

The hooks for holding the foil are activated automatically when the bale is being clamped, while their release occurs when the cutting jaw reaches its maximum opening position.

The cutter is equipped with welded cutting teeth made of wear-resistant steel, ensuring longer service life and maintaining sharpness over time. High quality forged tines guarantee durability and reliable performance, while the optimum cutting radius improves cutting efficiency.

BALE CUTTER

MBC

YouTube



180bar - 25L/min

469 kg



SPECIFICATION

- cutting bales up to 1520 mm high
- welded cutting teeth
- hooks for holding the foil
- high quality forged tines L-820 M28
- optimum cutting radius

OPTIONS

- flow divider valve - DFL

BALE CUTTER BOLT-ON TEETH

MBC-B



180bar - 25L/min

472 kg



SPECIFICATION

- cutting bales up to 1520 mm high
- bolt-on cutting teeth
- hooks for holding the foil
- high quality forged tines L-820 M28
- optimum cutting radius

OPTIONS

- flow divider valve - DFL

CHOPPER BUCKET

GENERAL INFORMATION

The chopping shovel is used for chopping root crops - sugar beet, potatoes, beetroot. Depending on the flap setting, you can get a chopped fraction size from 7cm to 2cm, finer chopping is possible when chopping the already processed material again. This is a very desirable device for the production of biogas or enriching silage piles with ingredients contained in root crops. The shovel is equipped with hydraulic protection in case the shaft is blocked by a stone. The standard design of the shovel allows you to bolt-on various types of mountings.

CHOPPER BUCKET

FRSB

YouTube





≠ 6 mm	≠ 6 mm	1,53 - 2,05 m³	180bar - 55L/min

SPECIFICATION

- adjustabe chop size
- central lubrication system
- cutting blades made of steel HB500
- 150x20 HB500 cutting edge
- only one hydraulic section required
- processing capacity 1000 kg/60s
- pressure relief valve VMP in standard
- recommended flow rate 55 L/min

INDEX	WIDTH	WEIGHT	VOL.
FRSB180	180 cm	1016 kg	1,53 m³
FRSB210	210 cm	1100 kg	1,79 m³
FRSB240	240 cm	1184 kg	2,05 m³



CUTTING BLADES MADE OF STEEL HB500



ADJUSTABE CHOP SIZE



ADAPTATION TO DIFFERENT TYPES OF BOLTED ATTACHMENTS

SELF LOADING BALE WRAPPER

GENERAL INFORMATION

OW3 bale wrappper is a very solid and simple construction. Manual steering is easy to handle, machine need very little maintenance. Loading the bale, wrapping, cutting the foil and laying it back on the field is done from operators cab in comparison with traditional stationary bale wrappers. Thanks to high durability and capacity, we can pick up a second bale while wrapping the first one to save operation time. Loading arm is adjustable. Wrapping time depends on size of the bale and how many layers are we willing to wrap, but on average it takes not longer than 1 minute to wrap a bale. Foil cutting blade is powered by hydraulic ram controled from the cabin. By the time of unloading bale is supported by a subframe that is relieving the forces acting on the main frame and lays the bale in a desired position. Only one hydraulic section is required to operate. Maximum weight of the bale that can be wrapper is 1150kg and another one can be handed.

SELF LOADING BALE WRAPPER

OW3

YouTube

180bar - 25L/min

2070 kg





SPECIFICATION

- maximum bale diameter 1800 mm
- maximum bale width 1350 mm
- allowable bale weight 1150 kg
- foil width 750 mm
- required tractor power 30 hp
- wrapping counter
- tires 340/55 R16

PRO Line

FUNCTION DESCRIPTION

LOADING ARM

It is adjustable for efficient gripping of bales of different diameters.

SUPPORTING SUB FRAME

While the bale is unloaded sub frame picks it up, rotates perpendicular to the axis and gently puts on the ground level, minimalizing risk of damaging the foil. It is possible as well to drop the bales in the same position as they were at the wrapping table.

FOIL DISPENSER

Modular sprocket wheels are responsible for the drives, alloy pipes with carving to stretch the foil, simple and user friendly mechanism to swap foil, 3 additional foil storage stands

WRAPPING TABLE

Wrapping table is settled on a massive 85mm pin, firmly sealed in a transmission drive gearbox which gives a long lifespan. 4 solid 8mm thick rubber belts, steel cover for chain sprockets, rubber cones positioning the bale in the working area of the foil feeder.

LOG GRAPPLES

LOG GRAPPLE R27

AG08-A





3000 kg | 148 kg

SPECIFICATION

- Gripping area 0.27m²
- Maximum gripper width: 1334 mm
- Minimum gripping diameter: 75 mm
- Sliding bushings in pivot points

OPTIONS

- any excavator mount
- adapter for rotator #40
- adapter for rotator #50
- adapter for rotator #60

LOG GRAPPLE R34

AG08-B





4000 kg | 244 kg

SPECIFICATION

- Gripping area 0.34m²
- Maximum gripper width: 1467 mm
- Minimum gripping diameter: 80 mm
- Sliding bushings in pivot points

OPTIONS

- any excavator mount
- adapter for rotator #40
- adapter for rotator #50
- adapter for rotator #60

LOG GRAPPLE R49

AG08-C





4800 kg | 303 kg

SPECIFICATION

- Gripping area 0.49m²
- Maximum gripper width: 1808 mm
- Minimum gripping diameter: 95 mm
- Sliding bushings in pivot points

OPTIONS

- any excavator mount
- adapter for rotator #40
- adapter for rotator #50
- adapter for rotator #60

FORESTRY

WOOD GRIPPER FOR PALLET TRUCK

UPG1



113 kg

SPECIFICATION

- FEM 2
- 1 hydraulic cylinder
- large range of working diameters

OPTIONS

- UPG1-B FEM 3

WOOD GRIPPER 1-ARM

UWG1



1000 kg

163 kg

SPECIFICATION

- 1 hydraulic cylinder
- large range of working diameters
- pressure relief valve - VMP as a standard

OPTIONS

- bolt-on picking teeth

WOOD GRIPPER 2-ARM

UWG2



1200 kg

243 kg

SPECIFICATION

- 2 independent feet
- 2 hydraulic cylinders
- large range of working diameters
- pressure relief valve - VMP as a standard

WOOD GRIPPER STANDARD

UWG3

1300 kg | 249 kg



SPECIFICATION

- 2 hydraulic cylinders
- large range of working diameters
- pressure relief valve - VMP as a standard
- sheet metal feet ≠ 20 mm
- 2 independent jaws

WOOD GRIPPER MAXI

UWG2M

3000 kg | 543 kg



SPECIFICATION

- 2 hydraulic cylinders
- large range of log diameters to be gripped
- pressure relief valve - VMP as a standard
- sheet metal feet ≠ 25 mm

WOOD GRIPPER GOLIAT

UWGPG

3500 kg | 618 kg



SPECIFICATION

- 2 hydraulic cylinders
- large range of log diameters to be gripped
- pressure relief valve - VMP as a standard
- sheet metal feet ≠ 25 mm
- reinforced feet

WOOD GRIPPER WITH FORKS

UPFWG

683 kg



SPECIFICATION

- 100x45x1200 3T FEM 3A fork as a standard
- 2 hydraulic cylinder
- large range of working diameters
- pressure relief valve - VMP as a standard
- tube reinforced feet

FORESTRY

FOREST RAKE

URFB

563 kg



SPECIFICATION

- construction based on 2 thick material tubes
- ground following
- replaceable tine tips
- foot for machine placement in a vertical position
- sealing sheets (see the picture)

OPTIONS

- available with alternating number of tines

FOREST RAKE PROFILED FRAME

URFBP

560 kg



SPECIFICATION

- profiled tine ends
- construction based on 2 thick material tubes
- ground following
- replaceable tine tips
- foot for machine placement in a vertical position
- sealing sheets (see the picture)

OPTIONS

- available with alternating number of tines

FOREST RAKE WITH GRAB

URFBD

YouTube

803 kg



SPECIFICATION

- grab for biomass laying
- construction based on 2 thick material tubes
- ground following
- replaceable tine tips
- foot for machine placement in a vertical position
- sealing sheets (see the picture)

OPTIONS

- available with alternating number of tines
- pressure relief valve - VMP

PRO Line

ACTIVE FOREST PLOUGH

AFP

YouTube



SPECIFICATION

- ploughing the furrow to the depth of about 450 mm
- furrow bottom loosening
- furrow bottom smoothing
- integrated PTO-powered hydraulic system
- adjusting the width of the ploughed furrow
- 150kg of weights
- spring loaded rear furrow

OPTIONS

- extra weights

150 kg OF WEIGHTS IN STANDARD

INTEGRATED PTO-POWERED HYDRAULIC SYSTEM

SWEEPING FLANGE

ROOT RIPPER

URTR

YouTube

470 kg





SPECIFICATION

- crimped foot against root slipping
- 2 independent feet
- 2 hydraulic cylinders

OPTIONS

- pressure relief valve - VMP

SPREADER

GENERAL INFORMATION

The main advantage of our sand spreaders is their self-loading function. A system of very precise dosing of the material thanks to stepless regulation of the material-taking shaft. There also is a rubber sealing with pressure plate that is allowing to tilt if a stone gets into lower part of the bucket to the dosing shaft. Additionally, the standard equipment includes a tarpaulin that protects the material in the container against weather conditions that could affect its properties. The metal grid inside the bucket protects the dosing system against stones or other undesirable fractions that may be present in the material being spread. Sand spreaders have built-in feet that allow the machine to be positioned vertically. We also make sand spreaders with other mountings dedicated to specific loaders, in that case the hydraulic ram is not mounted to the sand spreader.

SAND PADAWAN

SAND MASTER

SELFLOADING SYSTEM

ADJUSTABLE DOSING

GRID

RUBBER-SPRING SYSTEM

SPREADER SAND PADAWAN

SSP

≠ 5 mm | ≠ 4 mm | 0,22 - 0,31m³ | 120bar - 35L/min

SPECIFICATION

- standard mounting for three-point hitch (TUZ) cat. 0 & I
- selfloading system operated from cabin
- precise dosing on fixed width
- adjustable dosing
- grid separating larger fractions
- rubber-spring system passing larger fractions
- rain tarpaulin
- steel bearings protection

OPTIONS

- led lighting





INDEX	WIDTH	WEIGHT	POJ.	WORKING WIDTH
SSP120	135 cm	210 kg	0,22 m³	123 cm
SSP140	155 cm	230 kg	0,27 m³	143 cm
SSP160	175 cm	250 kg	0,31 m³	163 cm

SPREADER SAND MASTER

SSM

≠ 8 mm | ≠ 5 mm | 1,2 - 1,8m³ | 120bar - 35L/min

SPECIFICATION

- standard mounting for three-point hitch (TUZ) cat. II & III
- selfloading system operated from cabin
- precise dosing on fixed width
- adjustable dosing
- grid separating larger fractions
- rubber-spring system passing larger fractions
- rain tarpaulin
- steel bearings protection
- led lighting





INDEX	WIDTH	WEIGHT	POJ.	WORKING WIDTH
SSM160	184 cm	568 kg	1,20 m³	160 cm
SSM180	204 cm	610 kg	1,35 m³	180 cm
SSM200	224 cm	658 kg	1,50 m³	200 cm
SSM220	244 cm	718 kg	1,65 m³	220 cm
SSM240	264 cm	758 kg	1,80 m³	240 cm

SNOW PLOUGHS

GENERAL INFORMATION

Snow plows produced by us are available in a wide range of sizes, which makes it easier to match the appropriate equipment to your vehicle. Plows are available in straight and tilting versions, with the possibility of tilting the plow by +/- 30 degrees. All of them are standardly equipped with transverse and horizontal ground following. In order to make it easier for aggregating accessories to vehicles, we offer a system of many different mountings and frames. All plows also have a foldable clearing edge in case of collision with a curb or other obstacle that could damage the plow. The best effect of fighting with winter unpleaseaties with a plow is achieved in combination with a sand spreader, which are also in our offer.

SNOW PLOUGH STRAIGHT COMMUNAL

CPK





≠ 4 mm | ≠ 4 mm | 150x30

SPECIFICATION

- bent mouldboard
- mouldboard hydraulic control
- tilting blades
- ground following
- 26° right/left working angle
- sliding skids as standard

OPTIONS

- LED lighting

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPK120	120 cm	103 kg	107 - 120 cm
CPK150	150 cm	114 kg	135 - 151 cm
CPK180	180 cm	123 kg	163 - 184 cm

SNOW PLOUGH VARIO COMMUNAL

CPKV





≠ 4 mm | ≠ 4 mm | 150x30

SPECIFICATION

- mouldboard hydraulic control
- tilting blades
- ground following
- 30° right/left working angle

OPTIONS

- LED lighting
- support wheels from the 1,8 m
- sliding skids from the 1,8 m.
- remote control, supply voltage 12/24 V DC

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPKV130	130 cm	120 kg	114 - 132 cm
CPKV150	150 cm	129 kg	134 - 152 cm
CPKV180	180 cm	149 kg	164 - 182 cm
CPKV200	200 cm	159 kg	184 - 202 cm

SNOW PLOUGH STRAIGHT LIGHTWEIGHT

CPLH





≠ 6 mm | ≠ 4 mm | 150x30

SPECIFICATION

- bent mouldboard
- mouldboard hydraulic control
- tilting blades
- ground following
- 30° right/left working angle

OPTIONS

- LED lighting
- support wheels from the 1,8 m
- sliding skids from the 1,8 m

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPLH130	130 cm	125 kg	117 - 131 cm
CPLH150	150 cm	143 kg	132 - 151 cm
CPLH180	180 cm	163 kg	161 - 184 cm
CPLH200	200 cm	192 kg	176 - 201 cm

SNOW PLOUGH VARIO LIGHTWEIGHT

CPLV





≠ 6 mm | ≠ 4 mm | 150x30

SPECIFICATION

- mouldboard hydraulic control
- tilting blades
- ground following
- 30° right/left working angle

OPTIONS

- LED lighting
- support wheels from the 1,8 m
- sliding skids from the 1,8 m.
- extension
- remote control, supply voltage 12/24 V DC

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPLV150	150 cm	141 kg	133 - 151 cm
CPLV180	180 cm	173 kg	156 - 180 cm
CPLV200	200 cm	180 kg	173 - 201 cm

FK Machinery
BY KOŁASZEWSKI

SNOW PLOUGH STANDARD

CPSH





≠ 8 mm

≠ 4 mm

175x50

SPECIFICATION

- bent mouldboard
- mouldboard hydraulic control
- tilting blades
- ground following
- 30° right/left working angle

OPTIONS

- LED lighting
- support wheels
- sliding skids

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPSH200	200 cm	284 kg	177 - 202 cm
CPSH220	220 cm	311 kg	194 - 221 cm
CPSH260	260 cm	337 kg	224 - 260 cm
CPSH290	290 cm	370 kg	258 - 294 cm

SNOW PLOUGH VARIO STANDARD

CPSV





≠ 8 mm

≠ 4 mm

175x50

SPECIFICATION

- mouldboard hydraulic control
- tilting blades
- ground following
- 26° right/left working angle

OPTIONS

- LED lighting
- support wheels
- sliding skids
- remote control, supply voltage 12/24 V DC

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPSV200	200 cm	318 kg	186 - 202 cm
CPSV220	220 cm	326 kg	197 - 222 cm
CPSV260	260 cm	371 kg	238 - 263 cm
CPSV290	290 cm	401 kg	252 - 291 cm

SNOW PLOUGH STRAIGHT HEAVYWEIGHT

CPCH





≠ 10 mm

≠ 5 mm

175x50

SPECIFICATION

- bent mouldboard
- mouldboard hydraulic control
- tilting blades
- ground following
- 27° right/left working angle

OPTIONS

- LED lighting
- support wheels
- sliding skids

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPCH260	260 cm	479 kg	227 - 261 cm
CPCH290	290 cm	510 kg	275 - 294 cm
CPCH330	330 cm	544 kg	290 - 330 cm

SNOW PLOUGH VARIO HEAVYWEIGHT

CPCV







≠ 10 mm

≠ 5 mm

175x50

SPECIFICATION

- mouldboard hydraulic control
- tilting blades
- ground following
- 30° right/left working angle

OPTIONS

- LED lighting
- support wheels
- sliding skids
- remote control, supply voltage 12/24 V DC

INDEX	WIDTH	WEIGHT	WORKING WIDTH
CPCV260	260 cm	453 kg	228 - 261 cm
CPCV290	290 cm	474 kg	254 - 294 cm
CPCV330	330 cm	515 kg	291 - 331 cm

GENERAL INFORMATION

FALCON and X-WING snow plough series represent the premium heavy-duty attachments in their segment, engineered for professional users who demand maximum performance, durability, and reliability.

The mouldboard design, featuring an aggressive curvature profile, delivers outstanding snow rolling and discharge efficiency, even in the most demanding operating conditions. Reversible rubber cutting edges ensure extended service life and optimal utilization of the wear components.

Each unit is equipped as standard with a fully autonomous hydraulic system. A 24V electric power pack drives the hydraulic pump, eliminating the need for integration with the carrier vehicle's hydraulic system and ensuring complete operational independence.

All functions are controlled directly from the cab via an intuitive control panel, providing precise and responsive operation. The plough is mounted using a UNIMOG-compatible mounting plate, and thanks to its independent power supply, it can be quickly and safely attached by a single operator.

Superior ground following is achieved through an integrated floating system within the hydraulics, combined with a centrally positioned mouldboard pivot point. This design allows the plough to adapt seamlessly to terrain contours, both vertically and horizontally, ensuring consistent and efficient snow removal on uneven surfaces.

FALCON and X-WING series are designed for intensive professional use, where operational efficiency, durability, and reliability are critical.

SNOW PLOUGH FALCON

PH







SPECIFICATION

- hydraulic system with oil pump
- floating system
- mounting plate in UNIMOG standard
- turning angle 33.5°

OPTIONS

- LED road lights

INDEX	WIDTH	WEIGHT	WORKING WIDTH
PH30	300 cm	600 kg	243-300cm
PH33	330 cm	624 kg	263-330cm
PH35	350 cm	660 kg	293-350cm
PH38	380 cm	696 kg	323-380cm

SNOW PLOUGH X-WING

PJ









SPECIFICATION

- hydraulic system with oil pump
- floating system
- mounting plate in UNIMOG standard
- turning angle 28.5°

OPTIONS

- LED road lights

INDEX	WIDTH	WEIGHT	WORKING WIDTH
PJ29	290 cm	575 kg	252-290cm
PJ33	330 cm	615 kg	292-330cm
PJ35	350 cm	640 kg	312-350cm

ADDITIONAL ACCESSORIES

LIFTING SYSTEM

CSUM



FOR LIGHTWEIGHT SNOW PLOUGHS

- hydraulic lifting
- 396 mm lift range

CSUS



FOR STANDARD SNOW PLOUGHS

- hydraulic lifting
- 500 mm lift range

CSUC



FOR HEAVY SNOW PLOUGHS

- hydraulic lifting
- 538 mm lift range

FRAME



COMBI TUZ KAT. I i II, EURO



EURO



THREE-POINT HITCH CAT. II





FOR DIFFERENT MOUNTINGS



WITH HOLES FOR SCREWING IN THE FIXING

SPECIFICATION

- horizontal and vertical ground following

Our product range includes a wider selection of frames to fit practically every fixing to our snow ploughs

SUPPORT WHEEL

SPWS160/50



- used in CPK, CPKV, CPLH, CPLV
- 160 mm – wheel diameter
- 50 mm – wheel width
- 145 mm – adjustment range

SPWS200/40



- used in CPSH, CPSV
- 200 mm – wheel diameter
- 40 mm – wheel width
- 130 mm – adjustment range

SPWS200/60



- used in CPCH, CPCV
- 200 mm – wheel diameter
- 60 mm – wheel width
- 130 mm – adjustment range

SLIDING SKID

SU2



- sliding skid for a road plough

UNIVERSAL SLIDING SKID

SU1



- used for the lightweight, standard and heavy weight ploughs

VARIOUS TYPES CLEARING BLADES



- rubber blade: 150x30, 175x50
- steel blade: 150x12, 175x16, 175x18
- polyurethane blade: 150x30

LED

- LED light

DOZER BLADE SUPERLIGHT FOR TRACTOR REAR

CZTSL





≠ 6 mm | ≠ 5 mm | 100x12

SPECIFICATION

- right-left angle adjustment
- wheel height adjustment
- three-point hitch cat. I & 0
- HB500 steel blade
- support foot

INDEX	WIDTH	WEIGHT
CZTSL160	160 cm	190 kg

DOZER BLADE LIGHTWEIGHT FOR TRACTOR REAR

CZTLH





≠ 6 mm | ≠ 5 mm | 130x12

SPECIFICATION

- right-left angle adjustment
- wheel height adjustment
- three-point hitch cat. II
- HB500 steel blade
- support foot

OPTIONS

- mechanical version

INDEX	WIDTH	WEIGHT
CZTLH180	180 cm	290 kg
CZTLH210	210 cm	310 kg
CZTLH240	240 cm	330 kg
CZTLH270	270 cm	350 kg

DOZER BLADE HEAVYWEIGHT FOR TRACTOR REAR

CZTCH





≠ 8 mm | ≠ 6 mm | 200x12

SPECIFICATION

- right-left angle adjustment
- wheel height adjustment
- three-point hitch cat. II
- HB500 steel blade
- profiled mouldboard

OPTIONS

- mechanical version
- hydraulic accumulator

INDEX	WIDTH	WEIGHT
CZTCH240	240 cm	600 kg
CZTCH270	270 cm	630 kg
CZTCH300	300 cm	665 kg

DOZER BLADE HEAVYWEIGHT FOR TRACTOR REAR TILTED

CZTCW





≠ 8 mm | ≠ 6 mm | 200x12

SPECIFICATION

- right-left angle adjustment
- wheel height adjustment
- three-point hitch cat. II
- HB500 steel blade
- profiled mouldboard
- horizontal regulation
- swing angle by 7° to each side

OPTIONS

- hydraulic accumulator

INDEX	WIDTH	WEIGHT
CZTCW180	180 cm	590 kg
CZTCW240	240 cm	630 kg
CZTCW270	270 cm	656 kg
CZTCW300	300 cm	681 kg

MIXERS

GENERAL INFORMATION

Mixers are used to mix soil, fertilizers, seeds and other loose materials. Our mixers stand out for their drive transmission options. There are many configuration possibilities for the individual models that virtually all mixer aggregation scenarios are possible. Great customization options offer to set up them just as needed and improve the workflow.

HYDRAULIC

PTO



COMBI

ELECTRIC

MIXER WITH PTO DRIVE 600

UBCM600

69 rpm
7,75:1
466 kg
≠ 5 mm
≠ 6 mm
0,6 m³

SPECIFICATION

three-point hitch cat. II
pallet fork pockets

MIXER WITH PTO DRIVE 800

UBCM800

69 rpm
7,75:1
581 kg
≠ 5 mm
≠ 6 mm
0,8 m³



SPECIFICATION

- three-point hitch cat. II
- pallet fork pockets

MIXER WITH PTO DRIVE 1200

UBCM1200

50 rpm
10,8:1
830 kg
≠ 6 mm
≠ 8 mm
1,2 m³



SPECIFICATION

- three-point hitch cat. II
- pallet fork pockets
- 2 nozzles as a standard

OPTIONS ○ self-loading ○ additional chute

MIXER WITH HYDRAULIC DRIVE 600

UBCH600

35 rpm
912 Nm
511 kg
180bar - 65L/min
≠ 5 mm
≠ 8 mm
0,6 m³



SPECIFICATION

- three-point hitch cat. II
- motor ALSG6 400
- pallet fork pockets
- recommended flow rate 60-80 l/min (max 120 l/min)

MIXER WITH HYDRAULIC DRIVE 800

UBCH800

35 rpm
912 Nm
589 kg
180bar - 65L/min
≠ 5 mm
≠ 8 mm
0,8 m³



SPECIFICATION

- three-point hitch cat. II
- motor ALSG6 400cc
- pallet fork pockets
- recommended flow rate 60-80 l/min (max 120 l/min)

MIXER WITH HYDRAULIC DRIVE 1200

UBCH1200

35 rpm
912 Nm
789 kg
180bar - 65L/min
≠ 6 mm
≠ 8 mm
1,2 m³



SPECIFICATION

- three-point hitch cat. II
- motor ALSG6 400cc
- pallet fork pockets
- recommended flow rate 60-80 l/min (max 120 l/min)
- 2 nozzles as a standard

OPTIONS

- self-loading
- additional chute

MIXER COMBI (PTO AND HYDRAULICS) 600

UBCHM600

35 rpm
WOM
69 rpm
912 Nm
510 kg
180bar - 65L/min
≠ 5 mm
≠ 6 mm
0,6 m³



MIXER COMBI (PTO AND HYDRAULICS) 800

UBCHM800

35 rpm
WOM
69 rpm
912 Nm
581 kg
180bar - 65L/min
≠ 5 mm
≠ 6 mm
0,8 m³



MIXER COMBI (PTO AND HYDRAULICS) 1200

UBCHM1200

35 rpm
WOM
50 rpm
912 Nm
876 kg
180bar - 65L/min
≠ 6 mm
≠ 8 mm
1,2 m³



- 2 nozzles as a standard

SPECIFICATION

- three-point hitch cat. II
- pallet fork pockets
- motor ALSG6 400cc
- recommended flow rate 60-80 l/min (max 120 l/min)
- possibility of power supply from the hydraulic system or PTO shaft

OPTIONS

- self-loading
- additional chute

MIXER WITH ELECTRIC MOTOR 600

UBCE600

45 rpm | 0,6 m³
15 kW | ≠ 5 mm
740 kg | ≠ 6 mm



SPECIFICATION

- three-point hitch cat. II
- motor 15 kW 1400 rpm
- pallet fork pockets
- mixer mounted on a stand

MIXER WITH ELECTRIC MOTOR 800

UBCE800

45 rpm | 0,8 m³
15 kW | ≠ 5 mm
909 kg | ≠ 6 mm



SPECIFICATION

- three-point hitch cat. II
- motor 15 kW 1400 rpm
- pallet fork pockets
- mixer mounted on a stand

MIXER WITH ELECTRIC MOTOR 1200

UBCE1200

32 rpm | 1,2 m³
18,5 kW | ≠ 6 mm
1184 kg | ≠ 8 mm



SPECIFICATION

- three-point hitch cat. II
- motor 18,5 kW 1400 rpm
- pallet fork pockets
- mixer mounted on a stand
- 2 nozzles as a standard

OPTIONS ○ motor SIEMENS ○ inverter ○ self-loading ○ additional chute

MIXER WITH ELECTRIC MOTOR LOW TYPE 600

UBCEN600

45 rpm
15 kW
590 kg
≠ 5 mm
≠ 6 mm
0,6 m³



SPECIFICATION

- three-point hitch cat. II
- motor 15 kW 1400 rpm
- pallet fork pockets

MIXER WITH ELECTRIC MOTOR LOW TYPE 800

UBCEN800

45 rpm
15 kW
743 kg
≠ 5 mm
≠ 6 mm
0,8 m³



SPECIFICATION

- three-point hitch cat. II
- motor 15 kW 1400 rpm
- pallet fork pockets

MIXER WITH ELECTRIC MOTOR LOW TYPE 1200

UBCEN1200

32 rpm
18,5 kW
950 kg
≠ 6 mm
≠ 8 mm
1,2 m³



SPECIFICATION

- three-point hitch cat. II
- motor 18,5 kW 1400 rpm
- pallet fork pockets
- 2 nozzles as a standard

OPTIONS ○ motor SIEMENS ○ inverter ○ self-loading ○ additional chute

SELF-LOADER 600

600S

219 kg | 0,23 m³



SPECIFICATION

- self-loading function optional for every mixer
- 2 hydraulic cylinders

SELF-LOADER 800

800S

229 kg | 0,27 m³



SPECIFICATION

- self-loading function optional for every mixer
- 2 hydraulic cylinders

SELF-LOADER 1200

1200S

256 kg | 0,32 m³



SPECIFICATION

- self-loading function optional for every mixer
- 2 hydraulic cylinders

ADDITIONAL ACCESSORIES

DIFFERENT TYPES OF MIXING SHOVELS

STANDARD SHOVEL | HEAVY DUTY SHOVEL | SCRAPING SHOVEL



ADDITIONAL CHUTE



- additional chute makes the unloading more versatile
- additional chutes can be made in several combinations

ADJUSTABLE CHUTE



STANDARD - (reach 550 mm)

LONG - (reach 1100 mm)

- horizontal and vertical adjustment allows for more accurate unload of the mixed material

HYDRAULIC OPENING CHUTE



- opening of the chutes without need to leave the cabin
- various options for steering chute openings

ELECTRIC MOTORS

11 KW	15 KW	18 KW	22 KW
971rpm	1463 rpm	1467 rpm	1472 rpm

DIFFERETNT SIZE OF PULLEY WHEELS

- various dimensions of pulley wheels allows to increase mixing power

BUCKET CONCRETE MIXING

GENERAL INFORMATION

The UCMB mixing bucket has been designed for construction site applications where access to electric power is limited and precise handling of small quantities of concrete is required. Significant cost and time savings are achieved thanks to the ability to transport the mixed material directly to any location on site. Dosing is facilitated by a hydraulically controlled discharge gate and an optional discharge pipe. The mixing bucket is hydraulically driven and can be operated with any carrier machine equipped with its own hydraulic system.The extended front bottom section with a cutting edge allows for easy loading of aggregate directly from the pile, significantly accelerating the mixing process. An opening protective cover equipped with teeth for tearing bags enables fast and safe addition of dry materials into the concrete mix. Additionally, the bucket is equipped as standard with integrated mounting profiles, for which dedicated brackets are available, significantly expanding compatibility with a wide range of carrier machines. The extended front bottom section with a cutting edge allows for easy loading of aggregate directly from the pile, significantly accelerating the mixing process. An opening protective cover equipped with teeth for tearing bags enables fast and safe addition of dry materials into the concrete mix. Additionally, the bucket is equipped as standard with integrated mounting profiles, for which dedicated brackets are available, significantly expanding compatibility with a wide range of carrier machines.

BUCKET CONCRETE MIXING

UCMB

YouTube



≠ 12 mm | ≠ 8 mm | 0,44-0,68 m³ | 180bar - 40L/min

SPECIFICATION

- 150x20 HB500 cutting edge
- bottom reinforcements ≠ 15 mm
- hydraulic solenoid divider
- HB400 quality steel mixing paddle
- robust stone screening grate
- recommended flow rate 40 l/min
- 3rd hose to plug in free flow oil return port

OPTIONS

- antisplash cover
- discharge pipe 1500 mm

INDEX	WIDTH	WEIGHT	VOL.	WORKING WIDTH
UCMB140	140 cm	593 kg	0,44 m³	118 cm
UCMB170	170 cm	672 kg	0,53 m³	145 cm
UCMB200	200 cm	750 kg	0,62 m³	178 cm
UCMB220	220 cm	794 kg	0,68 m³	198 cm

SEALING SYSTEM

Bearings protected by a sealing system

DISCHARGE GATE

Hydraulically controlled discharge gate

MIXER

Profiled mixer made of HB500 steel

DISCHARGE PIPE

Optional discharge pipe of any length

SWEEPERS

GENERAL INFORMATION

Sweepers are designed to remove dirt from streets, squares, pavements, parking lots or other paved surfaces. A wide range of models and a wide range of options allow the user to configure the machine for their own needs. Stepless height adjustment system that maximizes sweeping performance and optimizes wear on working components. The mounting frame system allows you to connect the machine to virtually any model of loader or tractor. After appropriate configuration, depending on the model, it is possible to sweep snow in winter. Sweepers have a floating system that allows them to follow the ground independently of the loader or forklift. Thanks to the use of leveling springs, the mounting frames and the entire working assembly are constantly leveled, which increases the comfort of attaching and detaching the machine as well as the work itself. Main brush diameter 525 mm.

MAIN BRUSHES



CYLINDRICAL PPN + WIRE
polypropylene + corrugated wire

CYLINDRICAL PPN
polypropylene

YouTube

MANUAL/HYDRAULIC WASTE TANK

The tank allows you to collect waste, and then move and discharge it to the desired place.
The contact point of the tank with the ground is equipped with a polyurethane cutting edge that does not damage the ground. Mechanical and hydraulic tank emptying versions are available.

SIDE BRUSH

The side brush with diameter 600 mm is designed to sweep debris into the working area of the main brush, for example, from under a wall or curb.
It has versatile adjustment and a cushioned arm that yields when encountering obstacles, minimizing the risk of damage. Option of installing brushes on both sides.

WATER SPRINKLING SYSTEM

Sprinkling the swept area significantly reduces dust generation. This is extremely important when sweeping inside buildings where various types of installations should not be exposed to dust.
The nozzles have stream regulation, which gives control over the spray area. An important aspect is also the placement of sprinklers in the front, which gives better results in reducing dust.

SPECIFICATION

- terrain following
- support wheels Ø 200 mm
- pallet forks sockets
- working angle adjustment
- stepless brush height adjustment
- wire-polypropylene brush
- waste tank (mechanical or hydraulic)*1
- inspection hatches in the tank*1
- side brush (left or right) *2
- water sprinkler system *3
- 175L water tank *3

* 1 - version TANK 2 - version BRUSH 3 - version HYDRO

MINI BASIC



CY120-K 266 kg

CY150-K 280 kg

150bar - 25L/min

BASIC



CY180-K 321 kg

150bar - 25L/min

MAXI BASIC



CY230-K 368 kg

CY280-K 395 kg

150bar - 25L/min

MINI TANK



CY120-J 360 kg

CY150-J 375 kg

150bar - 25L/min

TANK



CY180-J 415 kg

150bar - 25L/min

MAXI TANK



CY230-J 470 kg

CY280-J 595 kg

150bar - 25L/min

MINI TANK BRUSH



CY120-B
390 kg

CY150-B
405 kg

150bar - 35L/min

TANK BRUSH



CY180-B
446 kg

150bar - 35L/min

MAXI TANK BRUSH



CY230-B
500 kg

CY280-B
645 kg

150bar - 35L/min

PRO Line

MINI TANK BRUSH HYDRO



CY120-A
436 kg

CY150-A
461 kg

150bar - 35L/min

TANK BRUSH HYDRO



CY180-A
487 kg

150bar - 35L/min

MAXI TANK BRUSH HYDRO



CY230-A
532 kg

CY280-A
690 kg

150bar - 35L/min

HEAVY FIELD HARROW

4 ROWS HYDRAULIC

YouTube

CHANGEABLE SKIDS

3 POINT HITCH SYSTEM
WITH FOLDABLE FRAME

DOUBLE SIDED HARROWS
COMBI TYPE



4 ROWS OF HARROWS

HEAVY FIELD HARROW 4 m - 4 ROWS HYDR.

WPH40

6,88 m²

480 kg





HEAVY FIELD HARROW 5,1 m - 4 ROWS HYDR.

WPH51

9,2 m²

570 kg





HEAVY FIELD HARROW 6,3 m - 4 ROWS HYDR.

WPH63

12,73 m²

702 kg





HEAVY FIELD HARROW 8 m - 4 ROWS HYDR.

WPH80

17,84 m²

885 kg





SPECIFICATION

- double sided harrows - combi type
- changeable skids
- hydraulic folding (2 cylinders)
- 4 rows of harrows
- frame made from S355 steel
- 3 point hitch system with foldable frame
- ≠ 8 mm bended levelling bar
- hydraulic lock - VBPDE
- WPH80 - strengthen 3 point hitch system frame

OPTIONS

- laser cutted harrow

IRON CAST HARROW

LASER CUTTED HARROW



EXCAVATOR BUCKETS

DIGGING BUCKET 1-1,9T

EBA



SPECIFICATION

- teeth model 3FU
- shell S355 J2 ≠ 5 mm
- sides S355 J2 ≠ 4 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 110x16

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBA025	250 mm	29 kg	22 L	3
EBA03	300 mm	31 kg	27 L	3
EBA04	400 mm	35 kg	39 L	3
EBA05	500 mm	41 kg	50 L	4
EBA06	600 mm	47 kg	62 L	5

DIGGING BUCKET 1,9-2,6T

EBB



SPECIFICATION

- teeth model 3FU
- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 5 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 110x16

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBB03	300 mm	41 kg	42 L	3
EBB04	400 mm	46 kg	61 L	3
EBB05	500 mm	52 kg	77 L	4
EBB06	600 mm	57 kg	99 L	5
EBB07	700 mm	63 kg	114 L	5

DIGGING BUCKET 2,6-3,5T

EBC



SPECIFICATION

- teeth model - 3FU
- frame S355 J2 ≠ 6 mm
- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 5 + 10 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBC025	250 mm	54 kg	40 L	3
EBC03	300 mm	59 kg	52 L	3
EBC04	400 mm	70 kg	76 L	3
EBC05	500 mm	81 kg	100 L	4
EBC06	600 mm	91 kg	127 L	5
EBC07	700 mm	101 kg	151 L	5
EBC08	800 mm	110 kg	177 L	6

DIGGING BUCKET 3,5-5T

EBD



SPECIFICATION

- teeth model 3FU
- frame S355 J2 ≠ 6 mm
- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 5 + 10 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBD03	300 mm	68 kg	67 L	3
EBD035	350 mm	73 kg	82 L	3
EBD04	400 mm	78 kg	97 L	3
EBD05	500 mm	91 kg	129 L	4
EBD06	600 mm	101 kg	161 L	5
EBD07	700 mm	112 kg	194 L	5
EBD08	800 mm	123 kg	230 L	6

DIGGING BUCKET 5-6T

EBE



SPECIFICATION

- teeth model 3FU
- frame S355 J2 ≠ 6 mm
- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 5 + 10 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBE03	300 mm	74 kg	74 L	3
EBE04	400 mm	85 kg	107 L	3
EBE05	500 mm	96 kg	141 L	4
EBE06	600 mm	108 kg	177 L	5
EBE07	700 mm	119 kg	210 L	5
EBE08	800 mm	130 kg	250 L	6
EBE09	900 mm	141 kg	290 L	7
EBE10	1000 mm	152 kg	323 L	7

DIGGING BUCKET 6-8,5T

EBF







≠ 6+12 mm	≠ 8 mm	≠ 6 mm	200x20	≠ 6 mm	JCB 531

SPECIFICATION

- teeth model - JCB 531
- cutting edge HB500 - 200x20
- shell S355 J2 - ≠ 8 mm
- frame S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 + 12 mm
- steel on side cutting edges HB400 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBF03	300 mm	100 kg	90 L	3
EBF04	400 mm	115 kg	130 L	3
EBF05	500 mm	131 kg	170 L	4
EBF06	600 mm	146 kg	210 L	4
EBF07	700 mm	162 kg	255 L	5
EBF08	800 mm	176 kg	300 L	5
EBF09	900 mm	191 kg	340 L	6
EBF10	1000 mm	206 kg	380 L	6

DIGGING BUCKET 8,5-10T

EBG







≠ 6+12 mm	≠ 8 mm	≠ 6 mm	200x20	≠ 6 mm	JCB 531

SPECIFICATION

- teeth model - JCB 531
- cutting edge HB500 - 200x20
- shell S355 J2 - ≠ 8 mm
- frame S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 + 12 mm
- steel on side cutting edges HB400 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBG03	300 mm	131 kg	105 L	3
EBG04	400 mm	148 kg	155 L	3
EBG05	500 mm	164 kg	200 L	4
EBG06	600 mm	181 kg	255 L	4
EBG07	700 mm	198 kg	305 L	5
EBG08	800 mm	214 kg	370 L	5
EBG09	900 mm	231 kg	425 L	6
EBG10	1000 mm	247 kg	480 L	6

DIGGING BUCKET 10-12T

EBH







≠ 8 mm	≠ 8 mm	≠ 15 mm	250x25	≠ 8 mm	CAT J200

SPECIFICATION

- teeth model - CAT J200
- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 8 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBH08	800 mm	315 kg	365 L	5
EBH10	1000 mm	361 kg	470 L	6
EBH12	1200 mm	407 kg	577 L	7

DIGGING BUCKET 12-14T

EBI





≠ 8+10 mm	≠ 8 mm	≠ 20 mm	250x25	≠ 8 mm	CAT J250

SPECIFICATION

- teeth model - CAT J250
- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 8 + 10 mm
- steel on side cutting edges HB400 - ≠ 20 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBI08	800 mm	409 kg	458 L	4
EBI10	1000 mm	470 kg	599 L	5
EBI12	1200 mm	531 kg	740 L	5

DIGGING BUCKET 14-18T

EBJ

YouTube





≠ 8+10 mm	≠ 10 mm	≠ 20+10 mm	300x30	≠ 10 mm	CAT J300

SPECIFICATION

- teeth model - CAT J300
- shell S355 J2 - ≠ 10 mm
- sides HB500 - ≠ 8 + 10 mm
- steel on side cutting edges HB400 - ≠ 20+10 mm
- cutting edge HB500 - 300x30
- frame HB400 - ≠ 10 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EBJ08	800 mm	538 kg	570 L	4
EBJ10	1000 mm	625 kg	760 L	4
EBJ12	1200 mm	712 kg	950 L	5

SKELETON BUCKET 1-1,9T

EEA





≠ 4 mm

≠ 5 mm

≠ 6 mm

110x16

3FU

SPECIFICATION

- teeth model 3FU
- shell S355 J2 ≠ 5 mm
- sides S355 J2 ≠ 4 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 110x16
- bar spacing 25 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEA025	250 mm	25 kg	22 L	3
EEA03	300 mm	27 kg	27 L	3
EEA04	400 mm	31 kg	39 L	3
EEA05	500 mm	34 kg	50 L	4
EEA06	600 mm	38 kg	62 L	5

SKELETON BUCKET 1,9-2,6T

EEB





≠ 5 mm

≠ 6 mm

≠ 6 mm

110x16

3FU

SPECIFICATION

- teeth model 3FU
- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 5 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 110x16
- bar spacing 25 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEB03	300 mm	37 kg	42 L	3
EEB04	400 mm	42 kg	60 L	3
EEB05	500 mm	47 kg	78 L	4
EEB06	600 mm	52 kg	97 L	5
EEB07	700 mm	57 kg	115 L	5

SKELETON BUCKET 2,6-3,5T

EEC





≠ 5+10 mm

≠ 6 mm

≠ 6 mm

150x16

≠ 8 mm

3FU

SPECIFICATION

- teeth model - 3FU
- rib S355 J2 ≠ 8 mm
- shell S355 J2 - ≠ 6 mm
- bar spacing 45 mm
- sides S355 J2 - ≠ 5 + 10 mm
- steel on side cutting edges HB400 - ≠ 6 mm
- cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEC025	250 mm	60 kg	40 L	2
EEC03	300 mm	67 kg	52 L	3
EEC04	400 mm	73 kg	76 L	3
EEC05	500 mm	80 kg	100 L	4
EEC06	600 mm	86 kg	127 L	5
EEC07	700 mm	92 kg	151 L	5
EEC08	800 mm	99 kg	177 L	6

SKELETON BUCKET 3,5-5T

EED





≠ 5+10 mm

≠ 6 mm

≠ 6 mm

150x16

≠ 10 mm

3FU

SPECIFICATION

- teeth model 3FU
- rib S355 J2 ≠ 10 mm
- shell S355 J2 ≠ 6 mm
- bar spacing 45 mm
- sides S355 J2 ≠ 5 + 10 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EED03	300 mm	71 kg	67 L	3
EED035	350 mm	77 kg	82 L	3
EED04	400 mm	83 kg	97 L	3
EED05	500 mm	94 kg	129 L	4
EED06	600 mm	106 kg	161 L	5
EED07	700 mm	118 kg	194 L	5
EED08	800 mm	129 kg	230 L	6

SKELETON BUCKET 5-6T

EEE





≠ 5+10 mm

≠ 6 mm

≠ 6 mm

150x16

≠ 10 mm

3FU

SPECIFICATION

- teeth model 3FU
- cutting edge HB500 150x16
- shell S355 J2 ≠ 6 mm
- rib S355 J2 ≠ 10 mm
- sides S355 J2 ≠ 5 + 10 mm
- bar spacing 48,5 mm
- steel on side cutting edges HB400 ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEE03	300 mm	82 kg	74 L	3
EEE04	400 mm	94 kg	107 L	3
EEE05	500 mm	107 kg	141 L	4
EEE06	600 mm	119 kg	177 L	5
EEE07	700 mm	131 kg	210 L	5
EEE08	800 mm	144 kg	250 L	6
EEE09	900 mm	156 kg	290 L	7
EEE10	1000 mm	169 kg	323 L	7

SKELETON BUCKET 6-8,5T

EEF







≠ 6+12 mm	≠ 8 mm	≠ 6 mm	200x20	≠ 10 mm	JCB 531

SPECIFICATION

- teeth model - JCB 531
- cutting edge HB500 - 200x20
- shell S355 J2 - ≠ 8 mm
- rib S355 J2 - ≠ 10 mm
- sides S355 J2 - ≠ 6 + 12 mm
- bar spacing 48,5 mm
- steel on side cutting edges HB400 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEF03	300 mm	119 kg	90 L	3
EEF04	400 mm	133 kg	130 L	3
EEF05	500 mm	147 kg	170 L	4
EEF06	600 mm	160 kg	210 L	5
EEF07	700 mm	174 kg	255 L	5
EEF08	800 mm	188 kg	300 L	5
EEF09	900 mm	202 kg	340 L	6
EEF10	1000 mm	216 kg	380 L	6

SKELETON BUCKET 8,5-10T

EEG







≠ 6+12 mm	≠ 8 mm	≠ 6 mm	200x20	≠ 12 mm	JCB 531

SPECIFICATION

- teeth model - JCB 531
- cutting edge HB500 - 200x20
- shell S355 J2 - ≠ 8 mm
- rib S355 J2 - ≠ 12 mm
- sides S355 J2 - ≠ 6 + 12 mm
- bar spacing 60 mm
- steel on side cutting edges HB400 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEG03	300 mm	138 kg	105 L	3
EEG04	400 mm	155 kg	155 L	3
EEG05	500 mm	172 kg	200 L	4
EEG06	600 mm	190 kg	255 L	5
EEG07	700 mm	207 kg	305 L	5
EEG08	800 mm	224 kg	370 L	5
EEG09	900 mm	241 kg	425 L	6
EEG10	1000 mm	258 kg	480 L	6

SKELETON BUCKET 10-12T

EEH







≠ 8+10 mm	≠ 10 mm	≠ 15+6 mm	250x25	≠ 12 mm	CAT J200

SPECIFICATION

- teeth model - CAT J200
- shell S355 J2 ≠ 10 mm
- sides S355 J2 - ≠ 8 + 10 mm
- steel on side cutting edges HB400 - ≠ 15+6 mm
- cutting edge HB500 - 250x25
- rib S355 J2 - ≠ 12 mm
- bar spacing 56 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEH08	800 mm	298 kg	400 L	5
EEH10	1000 mm	345 kg	540 L	6
EEH12	1200 mm	392 kg	680 L	7

SKELETON BUCKET 12-14T

EEI







≠ 8+10 mm	≠ 12 mm	≠ 20+6 mm	250x25	≠ 12 mm	CAT J250

SPECIFICATION

- teeth model - CAT J250
- shell S355 J2 ≠ 12 mm
- sides S355 J2 - ≠ 8 + 10 mm
- steel on side cutting edges HB400 - ≠ 20+6 mm
- cutting edge HB500 - 250x25
- rib S355 J2 - ≠ 12 mm
- bar spacing 64,5 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEI08	800 mm	430 kg	580 L	5
EEI10	1000 mm	500 kg	785 L	5
EEI12	1200 mm	570 kg	990 L	6

SKELETON BUCKET 14-18T

EEJ

YouTube

YouTube







≠ 8+10 mm	≠ 15 mm	≠ 25 mm	300x30	≠ 15 mm	CAT J300

SPECIFICATION

- teeth model - CAT J300
- shell S355 J2 ≠ 15 mm
- sides S355 J2 - ≠ 8 + 10 mm
- steel on side cutting edges HB400 - ≠ 25 mm
- cutting edge HB500 - 300x30
- rib S355 J2 - ≠ 15 mm
- bar spacing 75,5 mm

INDEX	WIDTH	WEIGHT	VOL.	NO. OF TEETH
EEJ08	800 mm	478 kg	670 L	4
EEJ10	1000 mm	566 kg	900 L	4
EEJ12	1200 mm	654 kg	1130 L	5

SORTING BUCKET 5-6T

ERE





SPECIFICATION

- bar Ø 25 mm
- sides S355 J2 – ≠ 5 mm
- steel on side cutting edges – HB400 ≠ 15 mm
- cutting edge HB500 – 150x20
- rib S355 J2 – ≠ 12 mm
- bar spacing 43 mm

INDEX	WIDTH	WEIGHT	VOL.
ERE10	1000 mm	143 kg	252 L
ERE11	1100 mm	152 kg	276 L
ERE12	1200 mm	161 kg	300 L

SORTING BUCKET 6-8,5T

ERF





SPECIFICATION

- bar Ø 25 mm
- sides S355 J2 – ≠ 5 mm
- steel on side cutting edges – HB400 ≠ 15 mm
- cutting edge HB500 – 200x20
- rib S355 J2 – ≠ 12 mm
- bar spacing 45 mm

INDEX	WIDTH	WEIGHT	VOL.
ERF10	1000 mm	175 kg	350 L
ERF11	1100 mm	186 kg	385 L
ERF12	1200 mm	197 kg	420 L
ERF13	1300 mm	208 kg	455 L
ERF14	1400 mm	219 kg	490 L

SORTING BUCKET 8,5-10T

ERG





SPECIFICATION

- bar Ø 30 mm
- sides S355 J2 – ≠ 5 mm
- steel on side cutting edges – HB400 ≠ 15 mm
- cutting edge HB500 – 200x20
- rib S355 J2 – ≠ 15 mm
- bar spacing 52 mm

INDEX	WIDTH	WEIGHT	VOL.
ERG12	1200 mm	269 kg	450 L
ERG13	1300 mm	284 kg	488 L
ERG14	1400 mm	299 kg	526 L
ERG15	1500 mm	314 kg	564 L

SORTING BUCKET 10-12T

ERH





SPECIFICATION

- bar Ø 30 mm
- sides S355 J2 – ≠ 6 mm
- steel on side cutting edges – HB400 ≠ 20 mm
- cutting edge HB500 – 250x25
- rib S355 J2 – ≠ 15 mm
- bar spacing 52 mm

INDEX	WIDTH	WEIGHT	VOL.
ERH14	1400 mm	375 kg	584 L
ERH15	1500 mm	394 kg	626 L
ERH16	1600 mm	413 kg	668 L

SORTING BUCKET 12-14T

ERI





SPECIFICATION

- bar Ø 35 mm
- sides S355 J2 – ≠ 8 mm
- steel on side cutting edges – HB400 ≠ 20 mm
- cutting edge HB500 – 250x25
- rib S355 J2 – ≠ 20 mm
- bar spacing 62 mm

INDEX	WIDTH	WEIGHT	VOL.
ERI16	1600 mm	537 kg	791 L
ERI17	1700 mm	558 kg	841 L
ERI18	1800 mm	579 kg	891 L

SORTING BUCKET 14-18T

ERJ





≠ 38 mm

≠ 8 mm

≠ 25 mm

300x30

≠ 20 mm

SPECIFICATION

- bar Ø 38 mm
- sides S355 J2 – ≠ 8 mm
- steel on side cutting edges – HB400 ≠ 25 mm
- cutting edge HB500 – 300x30
- rib S355 J2 – ≠ 20 mm
- bar spacing 60 mm

INDEX	WIDTH	WEIGHT	VOL.
ERJ16	1600 mm	699 kg	962 L
ERJ17	1700 mm	728 kg	1023 L
ERJ18	1800 mm	757 kg	1084 L

TRENCHING BUCKET 1-1,9T

EKA







SPECIFICATION

- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 5 mm
- steel on side cutting edges HB400 ≠ 6mm
- cutting edge HB500 110x16

INDEX	WIDTH	WEIGHT	VOL.
EKA025	250 mm	28 kg	33 L
EKA03	300 mm	30 kg	40 L
EKA035	350 mm	32 kg	46 L

TRENCHING BUCKET 1,9-2,6T

EKB







SPECIFICATION

- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 5 + 8 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT	VOL.
EKB025	250 mm	37 kg	41 L
EKB03	300 mm	40 kg	50 L
EKB035	350 mm	43 kg	59 L

TRENCHING BUCKET 2,6-3,5T

EKC







SPECIFICATION

- shell S355 J2 ≠ 6
- sides S355 J2 ≠ 5 + 10 mm
- steel on side cutting edges HB400 ≠ 6mm
- cutting edge HB500 150x20
- frame S355 J2 ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
EKC025	250 mm	46 kg	46 L
EKC03	300 mm	51 kg	58 L
EKC035	350 mm	55 kg	70 L
EKC04	400 mm	60 kg	81 L

TRENCHING BUCKET 3,5-5T

EKD



SPECIFICATION

- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 5+10 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 150x20
- frame S355 J2 ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
EKD03	300 mm	69 kg	67 L
EKD035	350 mm	74 kg	82 L
EKD04	400 mm	79 kg	97 L
EKD045	450 mm	84 kg	129 L

TRENCHING BUCKET 5-6T

EKE





SPECIFICATION

- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 6 + 10mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 150x20
- frame S355 J2 ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
EKE03	300 mm	74 kg	91 L
EKE035	350 mm	80 kg	109 L
EKE04	400 mm	85 kg	127 L
EKE045	450 mm	91 kg	144 L
EKE05	500 mm	96 kg	162 L

TRENCHING BUCKET 6-8,5T

EKF



≠ 6+12 mm	≠ 8 mm	≠ 6 mm	200x20	≠ 6 mm

SPECIFICATION

- shell S355 J2 ≠ 8 mm
- sides S355 J2 ≠ 6 + 12 mm
- steel on side cutting edges HB400 ≠ 6 mm
- cutting edge HB500 200x20
- frame S355 J2 ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
EKF035	350 mm	113 kg	128 L
EKF04	400 mm	120 kg	149 L
EKF045	450 mm	127 kg	169 L
EKF05	500 mm	134 kg	190 L
EKF055	550 mm	143 kg	211 L

TRENCHING BUCKET 8,5-10T

EKG



≠ 6+12 mm	≠ 8 mm	≠ 8 mm	200x20	≠ 6 mm

SPECIFICATION

- shell S355 J2 ≠ 8 mm
- sides S355 J2 ≠ 6 +12 mm
- steel on side cutting edges HB400 - ≠ 8mm
- cutting edge HB500 200x20
- frame S355 J2 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
EKG04	400 mm	137 kg	182 L
EKG045	450 mm	152 kg	194 L
EKG05	500 mm	169 kg	206 L
EKG055	550 mm	184 kg	219 L
EKG06	600 mm	201 kg	231 L

TRENCHING BUCKET 10-12T

EKH



≠ 6+8 mm	≠ 8 mm	≠ 15 mm	250x25	≠ 8 mm

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides HB500 - ≠ 6+8 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.
EKH04	400 mm	159 kg	160 L
EKH045	450 mm	168 kg	185 L
EKH05	500 mm	177 kg	210 L

TRENCHING BUCKET 12-14T

EKI



≠ 6 + 8 mm	≠ 10 mm	≠ 20 mm	250x25	≠ 8 mm

SPECIFICATION

- shell S355 J2 - ≠ 10mm
- sides HB500 - ≠ 6 + 8 mm
- steel on side cutting edges HB400 - ≠ 20 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.
EKI04	400 mm	206 kg	194 L
EKI045	450 mm	219 kg	226 L
EKI05	500 mm	232 kg	258 L

TRENCHING BUCKET 14-18T

EKJ

YouTube



≠ 6 +10 mm	≠ 10 mm	≠ 20 mm	300x30	≠ 10 mm

SPECIFICATION

- shell S355 J2 - ≠ 10 mm
- sides HB500 - ≠ 6 + 10 mm
- steel on side cutting edges HB400 - ≠ 20 mm
- cutting edge HB500 - 300x30
- frame HB400 - ≠ 10 mm

INDEX	WIDTH	WEIGHT	VOL.
EKJ045	450 mm	315 kg	307 L
EKJ05	500 mm	331 kg	350 L
EKJ055	550 mm	347 kg	393 L

DITCHING BUCKET 1,9-2,6T

EDB

EDB-B







SPECIFICATION

- shell S355 J2 - ≠ 5 mm
- sides S355 J2 - ≠ 4 mm
- steel on side cutting edges HB400 - ≠ 8 mm
- cutting edge HB500 - 110x16
- * EDB-B additional cutting edge HB400 75x8

INDEX	WIDTH	WEIGHT EDB	WEIGHT EDB-B	VOL.
EDB085	850 mm	55 kg	60 kg	70 L
EDB10	1000 mm	62 kg	67 kg	82 L
EDB12	1200 mm	71 kg	77 kg	100 L

DITCHING BUCKET 2,6-3,5T

EDC

EDC-B







SPECIFICATION

- shell S355 J2 - ≠ 5 mm
- sides S355 J2 - ≠4 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x16
- * EDC-B additional cutting edge HB400 100x10

INDEX	WIDTH	WEIGHT EDC	WEIGHT EDC-B	VOL.
EDC10	1000 mm	82 kg	91 kg	128 L
EDC12	1200 mm	94 kg	103 kg	156 L
EDC14	1400 mm	117 kg	126 kg	185 L
EDC15	1500 mm	122 kg	131 kg	200 L
EDC16	1600 mm	131 kg	140 kg	213 L

DITCHING BUCKET 3,5-5T

EDD

EDD-B







SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 5 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x16
- * EDD-B additional cutting edge HB400 100x10

INDEX	WIDTH	WEIGHT EDD	WEIGHT EDD-B	VOL.
EDD10	1000 mm	92 kg	102 kg	142 L
EDD12	1200 mm	106 kg	116 kg	175 L
EDD14	1400 mm	120 kg	131 kg	207 L
EDD16	1600 mm	127 kg	138 kg	223 L
EDD18	1800 mm	134 kg	145 kg	240 L

DITCHING BUCKET 5-6T

EDE

EDE-B





SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x20
- * EDE-B additional cutting edge HB400 100x12

INDEX	WIDTH	WEIGHT EDE	WEIGHT EDE-B	VOL.
EDE10	1000 mm	110 kg	121 kg	156 L
EDE12	1200 mm	124 kg	135 kg	192 L
EDE14	1400 mm	138 kg	151 kg	227 L
EDE15	1500 mm	146 kg	163 kg	245 L
EDE16	1600 mm	153 kg	169 kg	263 L

DITCHING BUCKET 6-8,5T

EDF

EDF-B





SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 12 mm
- cutting edge HB500 - 200x20
- frame S355 J2 - ≠ 6 mm
- * EDF-B additional cutting edge HB400 120x12

INDEX	WIDTH	WEIGHT EDF	WEIGHT EDF-B	VOL.
EDF14	1400 mm	203 kg	220 kg	282 L
EDF15	1500 mm	214 kg	234 kg	304 L
EDF16	1600 mm	225 kg	246 kg	326 L
EDF18	1800 mm	236 kg	258 kg	370 L

DITCHING BUCKET 8,5-10T

EDG

EDG-B



≠ 6 mm	≠ 6 mm	≠ 12 mm	200x20	≠ 6 mm

SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 12 mm
- cutting edge HB500 - 200x20
- frame S355 J2 - ≠ 6 mm
- * EDG-B additional cutting edge HB400 140x12

INDEX	WIDTH	WEIGHT EDG	WEIGHT EDG-B	VOL.
EDG15	1500 mm	244 kg	266 kg	345 L
EDG16	1600 mm	255 kg	276 kg	370 L
EDG18	1800 mm	277 kg	299 kg	420 L

DITCHING BUCKET 10-12T

EDH

EDH-B



≠ 6 mm	≠ 6 mm	≠ 12 mm	200x20	≠ 6 mm

SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 12 mm
- cutting edge HB500 - 200x20
- frame HB400 - ≠ 6 mm
- *EDH-B additional cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT EDH	WEIGHT EDH-B	VOL.
EDH16	1600 mm	270 kg	298 kg	404 L
EDH18	1800 mm	296 kg	326 kg	457 L
EDH20	2000 mm	322 kg	354 kg	510 L

DITCHING BUCKET 12-14T

EDI

EDI-B



≠ 6 mm	≠ 8 mm	≠ 15 mm	250x25	≠ 8 mm

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm
- *EDI-B additional cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT EDI	WEIGHT EDI-B	VOL.
EDI18	1800 mm	393 kg	427 kg	552 L
EDI20	2000 mm	430 kg	468 kg	616 L

DITCHING BUCKET 14-18T

EDJ

YouTube

EDJ-B



≠ 8 mm	≠ 8 mm	≠ 18 mm	250x25	≠ 8 mm

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 8 mm
- steel on side cutting edges HB400 - ≠ 18 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm
- * EDJ-B additional cutting edge HB500 150x16

INDEX	WIDTH	WEIGHT EDJ	WEIGHT EDJ-B	VOL.
EDJ18	1800 mm	420 kg	462 kg	610 L
EDJ20	2000 mm	460 kg	504 kg	690 L

HYDRAULIC TILT DITCHING BUCKET 1,9-2,6T

EGB

EGB-B



SPECIFICATION

- shell S355 J2 - ≠ 5 mm
- sides S355 J2 - ≠ 4 mm
- steel on side cutting edges HB400 - ≠ 8 mm
- cutting edge HB500 - 110x16
- * EGB-B additional cutting edge HB400 75x8
- tilt ±36º

INDEX	WIDTH	WEIGHT EGB	WEIGHT EGB-B	VOL.
EGB085	850 mm	83 kg	88 kg	70 L
EGB10	1000 mm	95 kg	100 kg	82 L
EGB12	1200 mm	100 kg	106 kg	100 L

HYDRAULIC TILT DITCHING BUCKET 2,6-3,5T

EGC

EGC-B



SPECIFICATION

- shell S355 J2 - ≠ 5 mm
- sides S355 J2 - ≠4 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x16
- * EGC-B additional cutting edge HB400 100x10
- tilt ±36º

INDEX	WIDTH	WEIGHT EGC	WEIGHT EGC-B	VOL.
EGC10	1000 mm	115 kg	125 kg	128 L
EGC12	1200 mm	128 kg	139 kg	156 L
EGC14	1400 mm	142 kg	153 kg	185 L
EGC15	1500 mm	148 kg	160 kg	200 L
EGC16	1600 mm	155 kg	168 kg	213 L

HYDRAULIC TILT DITCHING BUCKET 3,5-5T

EGD

EGD-B



SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 5 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x16
- * EGD-B additional cutting edge HB400 100x10
- tilt ±43,5º

INDEX	WIDTH	WEIGHT EGD	WEIGHT EGD-B	VOL.
EGD10	1000 mm	143 kg	153 kg	142 L
EGD12	1200 mm	149 kg	159 kg	175 L
EGD13	1300 mm	160 kg	170 kg	190 L
EGD14	1400 mm	163 kg	173 kg	207 L
EGD15	1500 mm	170 kg	188 kg	223 L
EGD16	1600 mm	177 kg	199 kg	240 L

HYDRAULIC TILT DITCHING BUCKET 5-6T

EGE

EGE-B



SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x20
- * EGE-B additional cutting edge HB400 100x12
- tilt ±43,5º

INDEX	WIDTH	WEIGHT EGE	WEIGHT EGE-B	VOL.
EGE10	1000 mm	152 kg	163 kg	156 L
EGE12	1200 mm	159 kg	171 kg	192 L
EGE14	1400 mm	164 kg	176 kg	227 L
EGE15	1500 mm	182 kg	195 kg	245 L
EGE16	1600 mm	190 kg	205 kg	263 L

HYDRAULIC TILT DITCHING BUCKET 6-8,5T

EGF

EGF-B



SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 12 mm
- cutting edge HB500 - 200x20
- frame S355 J2 - ≠ 6 mm
- 2 hydraulic cylinders
- * EGF-B additional cutting edge HB400 120x12
- tilt ±42º

INDEX	WIDTH	WEIGHT EGF	WEIGHT EGF-B	VOL.
EGF14	1400 mm	278 kg	292 kg	282 L
EGF15	1500 mm	299 kg	316 kg	304 L
EGF16	1600 mm	311 kg	329 kg	326 L
EGF17	1700 mm	323 kg	342 kg	348 L
EGF18	1800 mm	335 kg	354 kg	370 L

HYDRAULIC TILT DITCHING BUCKET 8,5-10T

EGG

EGG-B



42,5°

≠ 6 mm | ≠ 6 mm | ≠ 12 mm | 200x20 | ≠ 6 mm

SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 12 mm
- cutting edge HB500 - 200x20
- frame S355 J2 - ≠ 6 mm
- 2 hydraulic cylinders
- * EGG-B additional cutting edge HB400 140x12
- tilt ±42,5°

INDEX	WIDTH	WEIGHT EGG	WEIGHT EGG-B	VOL.
EGG15	1500 mm	310 kg	331 kg	345 L
EGG16	1600 mm	322 kg	344 kg	370 L
EGG18	1800 mm	346 kg	369 kg	420 L

HYDRAULIC TILT DITCHING BUCKET 10-12T

EGH

EGH-B



42,5°

≠ 6 mm | ≠ 6 mm | ≠ 12 mm | 200x20 | ≠ 6 mm

SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 12 mm
- cutting edge HB500 - 200x20
- frame HB400 - ≠ 6 mm
- 2 hydraulic cylinders
- * EGH-B additional cutting edge HB500 150x16
- tilt ±42,5°

INDEX	WIDTH	WEIGHT EGH	WEIGHT EGH-B	VOL.
EGH16	1600 mm	366 kg	396 kg	404 L
EGH18	1800 mm	392 kg	430 kg	457 L

HYDRAULIC TILT DITCHING BUCKET 12-14T

EGI

EGI-B



35°

≠ 6 mm | ≠ 8 mm | ≠ 15 mm | 250x25 | ≠ 8 mm

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm
- 2 hydraulic cylinders
- * EGI-B additional cutting edge HB500 150x16
- tilt ±35°

INDEX	WIDTH	WEIGHT EGI	WEIGHT EGI-B	VOL.
EGI18	1800 mm	520 kg	555 kg	552 L
EGI20	2000 mm	554 kg	590 kg	616 L

HYDRAULIC TILT DITCHING BUCKET 14-18T

EGJ

EGJ-B



34,5°

≠ 8 mm | ≠ 8 mm | ≠ 18 mm | 250x25 | ≠ 8 mm

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 8 mm
- steel on side cutting edges HB400 - ≠ 18 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm
- 2 hydraulic cylinders
- * EGJ-B additional cutting edge HB500 150x16
- tilt ±34,5°

INDEX	WIDTH	WEIGHT EGJ	WEIGHT EGJ-B	VOL.
EGJ18	1800 mm	599 kg	643 kg	610 L
EGJ20	2000 mm	638 kg	689 kg	690 L

SCANDINAVIAN BUCKETS

SCANDINAVIAN BUCKET 3,5-5T

ESD





SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x16
- frame S355 J2 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
ESD12	1200 mm	147 kg	248 L
ESD14	1400 mm	163 kg	260 L

SCANDINAVIAN BUCKET 5-6T

ESE





SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 12 mm
- cutting edge HB500 - 150x20
- frame HB400 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
ESE14	1400 mm	205 kg	315 L
ESE16	1600 mm	227 kg	343 L

SCANDINAVIAN BUCKET 6-8,5T

ESF





SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 200x20
- frame S355 J2 - ≠ 6 mm

INDEX	WIDTH	WEIGHT	VOL.
ESF12	1200 mm	235 kg	330 L
ESF13	1300 mm	249 kg	364 L
ESF14	1400 mm	263 kg	398 L

SCANDINAVIAN BUCKET 8,5-10T

ESG





SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 250x25
- frame S355 J2 - ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.
ESG14	1400 mm	327 kg	457 L
ESG15	1500 mm	345 kg	500 L
ESG16	1600 mm	363 kg	543 L

SCANDINAVIAN BUCKET 10-12T

ESH





SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 8 mm
- steel on side cutting edges HB400 - ≠20 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.
ESH14	1400 mm	382 kg	582 L
ESH15	1500 mm	401 kg	640 L
ESH16	1600 mm	420 kg	698 L

SCANDINAVIAN BUCKET 12-14T

ESI



SPECIFICATION

- shell S355 J2 - ≠ 10 mm
- sides S355 J2 - ≠ 8 mm
- steel on side cutting edges HB400 - ≠ 20 mm
- cutting edge HB500 - 250x25
- frame S355 J2 - ≠ 8 mm

INDEX	WIDTH	WEIGHT	VOL.
ESI14	1400 mm	475 kg	695 L
ESI15	1500 mm	500 kg	766 L
ESI16	1600 mm	525 kg	837 L

SCANDINAVIAN BUCKET 14-18T

ESJ

YouTube
YouTube





SPECIFICATION

- shell S355 J2 - ≠ 10 mm
- sides S355 J2 - ≠ 10 mm
- steel on side cutting edges HB400 - ≠ 25 mm
- cutting edge HB500 - 300x30
- frame HB400 - ≠ 10 mm

INDEX	WIDTH	WEIGHT	VOL.
ESJ15	1500 mm	594 kg	860 L
ESJ16	1600 mm	623 kg	935 L
ESJ17	1700 mm	652 kg	1010 L

HYDRAULIC TILTING SCANDINAVIAN BUCKET

HYDRAULIC TILTING SCANDINAVIAN BUCKET 3,5-5T

ESD-B





≠ 6 mm	≠ 6 mm	≠ 10 mm	150x16	≠ 6 mm	43,5°

SPECIFICATION

- shell S355 J2 - ≠ 6 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 10 mm
- cutting edge HB500 - 150x16
- frame S355 J2 - ≠ 6 mm
- tilt ± 43,5°

INDEX	WIDTH	WEIGHT	VOL.
ESD12-B	1200 mm	191 kg	248 L
ESD14-B	1400 mm	207 kg	260 L

HYDRAULIC TILTING SCANDINAVIAN BUCKET 5-6T

ESE-B





≠ 6 mm	≠ 6 mm	≠ 12 mm	150x20	≠ 6 mm	43,5°

SPECIFICATION

- shell S355 J2 ≠ 6 mm
- sides S355 J2 ≠ 6 mm
- steel on side cutting edges HB400 ≠ 12 mm
- cutting edge HB500 - 150x20
- frame HB400 ≠ 6 mm
- tilt ± 43,5°

INDEX	WIDTH	WEIGHT	VOL.
ESE14-B	1400 mm	243 kg	315 L
ESE16-B	1600 mm	259 kg	343 L

HYDRAULIC TILTING SCANDINAVIAN BUCKET 6-8,5T

ESF-B



≠ 6 mm	≠ 8 mm	≠ 15 mm	200x20	≠ 6 mm	43,5°

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 200x20
- frame S355 J2 - ≠ 6 mm
- tilt: 43.5°

INDEX	WIDTH	WEIGHT	VOL.
ESF14-B	1400 mm	298 kg	330 L
ESF15-B	1500 mm	318 kg	364 L
ESF16-B	1600 mm	338 kg	398 L

HYDRAULIC TILTING SCANDINAVIAN BUCKET 8,5-10T

ESG-B



≠ 6 mm	≠ 8 mm	≠ 15 mm	250x25	≠ 8 mm	43,5°

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 6 mm
- steel on side cutting edges HB400 - ≠ 15 mm
- cutting edge HB500 - 250x25
- frame S355 J2 - ≠ 8 mm
- tilt: 43.5°

INDEX	WIDTH	WEIGHT	VOL.
ESG14-B	1400 mm	442 kg	457 L
ESG15-B	1500 mm	465 kg	500 L
ESG16-B	1600 mm	483 kg	543 L

HYDRAULIC TILTING SCANDINAVIAN BUCKET 10-12T

ESH-B



≠ 8 mm	≠ 8 mm	≠ 20 mm	250x25	≠ 8 mm	43,5°

SPECIFICATION

- shell S355 J2 - ≠ 8 mm
- sides S355 J2 - ≠ 8 mm
- steel on side cutting edges HB400 - ≠20 mm
- cutting edge HB500 - 250x25
- frame HB400 - ≠ 8 mm
- tilt: 43.5°

INDEX	WIDTH	WEIGHT	VOL.
ESH14-B	1400 mm	502 kg	582 L
ESH15-B	1500 mm	522 kg	640 L
ESH16-B	1600 mm	542 kg	698 L

HYDRAULIC TILTING SCANDINAVIAN BUCKET 12-14T

ESI-B



≠ 8 mm	≠ 10 mm	≠ 20 mm	250x25	≠ 8 mm	36,5°

SPECIFICATION

- shell S355 J2 - ≠ 10 mm
- sides S355 J2 - ≠ 8 mm
- steel on side cutting edges HB400 - ≠ 20 mm
- cutting edge HB500 - 250x25
- frame S355 J2 - ≠ 8 mm
- tilt: 36.5°

INDEX	WIDTH	WEIGHT	VOL.
ESI15-B	1500 mm	700 kg	766 L
ESI16-B	1600 mm	725 kg	837 L
ESI17-B	1700 mm	751 kg	870 L

HYDRAULIC TILTING SCANDINAVIAN BUCKET 14-18T

ESJ-B



≠ 10 mm	≠ 10 mm	≠ 25 mm	300x30	≠ 10 mm	36,5°

SPECIFICATION

- shell S355 J2 - ≠ 10 mm
- sides S355 J2 - ≠ 10 mm
- steel on side cutting edges HB400 - ≠ 25 mm
- cutting edge HB500 - 300x30
- frame HB400 - ≠ 10 mm
- tilt: 36.5°

INDEX	WIDTH	WEIGHT	VOL.
ESJ16-B	1600 mm	793 kg	935 L
ESJ17-B	1700 mm	823 kg	1010 L

TAPERED DITCHING BUCKET 1-3,5T

EWA



≠ 6 mm	≠ 6 mm	12x100	16x110

SPECIFICATION

- HB500 steel on side cutting edges along the entire length
- shell S355 J2 - ≠ 6 mm
- thick wall pipe Ø60 mm

INDEX	WIDTH	WEIGHT	VOL.
EWA11	1100 mm	75 kg	60 L

TAPERED DITCHING BUCKET 3,5-6T

EWB



≠ 6 mm	≠ 6 mm	16x110	16x150

SPECIFICATION

- HB500 steel on side cutting edges along the entire length
- shell S355 J2 - ≠ 6 mm
- thick wall pipe Ø70 mm

INDEX	WIDTH	WEIGHT	VOL.
EWB15	1500 mm	115 kg	145 L

TAPERED DITCHING BUCKET 6-10T

EWC



≠ 6 mm	≠ 6 mm	16x150	20x200

SPECIFICATION

- HB500 steel on side cutting edges along the entire length
- shell S355 J2 - ≠ 6 mm
- thick wall pipe Ø 80 mm

INDEX	WIDTH	WEIGHT	VOL.
EWC19	1900 mm	186 kg	284 L

TAPERED DITCHING BUCKET 10-14T

EWD



≠ 8 mm	≠ 8 mm	20x200	25x250

SPECIFICATION

- HB500 steel on side cutting edges along the entire length
- shell S355 J2 - ≠ 8 mm
- thick wall pipe Ø108 mm

INDEX	WIDTH	WEIGHT	VOL.
EWD26	2600 mm	325 kg	358 L

TAPERED DITCHING BUCKET 14-18T

EWE



≠ 10 mm	≠ 10 mm	20x200	25x250

SPECIFICATION

- HB500 steel on side cutting edges along the entire length
- shell S355 J2 - ≠ 10 mm
- thick wall pipe Ø132 mm

INDEX	WIDTH	WEIGHT	VOL.
EWE30	3000 mm	551 kg	654 L

HYDRAULIC TAPERED DITCHING BUCKET 1-3,5T

EWA-B





≠ 6 mm	≠ 6 mm	12x110	16x110	37,5°

SPECIFICATION

- HB500 steel on side cutting edges along the entire length,
- tilt ±37.5°
- shell S355 J2 - ≠ 6 mm
- Thick Wall Pipe Ø60 mm

INDEX	WIDTH	WEIGHT	VOL.
EWA11-B	1100 mm	101 kg	60 L

HYDRAULIC TAPERED DITCHING BUCKET 3,5-6T

EWB-B





≠ 6 mm	≠ 6 mm	16x110	16x150	42,5°

SPECIFICATION

- HB500 steel on side cutting edges along the entire length,
- tilt ±42.5°
- shell S355 J2 - ≠ 6 mm
- Thick Wall Pipe Ø70mm

INDEX	WIDTH	WEIGHT	VOL.
EWB15-B	1500 mm	152 kg	145 L

HYDRAULIC TAPERED DITCHING BUCKET 6-10T

EWC-B





≠ 6 mm	≠ 6 mm	16x150	20x200	42,5°

SPECIFICATION

- HB500 steel on side cutting edges along the entire length,
- tilt ±42.5°
- shell S355 J2 - ≠ 6 mm
- Thick Wall Pipe Ø80 mm

INDEX	WIDTH	WEIGHT	VOL.
EWC19-B	1900 mm	268 kg	284 L

HYDRAULIC TAPERED DITCHING BUCKET 10-14T

EWD-B





≠ 8 mm	≠ 8 mm	20x200	25x250	32,5°

SPECIFICATION

- HB500 steel on side cutting edges along the entire length,
- tilt ±32.5°
- shell S355 J2 - ≠ 8 mm
- Thick Wall Pipe Ø108 mm

INDEX	WIDTH	WEIGHT	VOL.
EWD26-B	2600 mm	459 kg	358 L

HYDRAULIC TAPERED DITCHING BUCKET 14-18T

EWE-B





≠ 10 mm	≠ 10 mm	20x200	25x250	32,5°

SPECIFICATION

- HB500 steel on side cutting edges along the entire length,
- tilt ±32.5°
- shell S355 J2 - ≠ 10 mm
- Thick Wall Pipe Ø132 mm

INDEX	WIDTH	WEIGHT	VOL.
EWE30-B	3000 mm	685 kg	654 L

RIPPER 1-1,9T

EFA





SPECIFICATION

- teeth model - CAT J200
- core S355 J2 ≠ 25 mm

39 kg | CAT J200

RIPPER 1,9-3,5T

EFB





SPECIFICATION

- teeth model - CAT J200
- core S355 J2 ≠ 30 mm

53 kg | CAT J200

RIPPER 3,5-6T

EFC





SPECIFICATION

- teeth model - CAT J200
- core S355 J2 ≠ 30 + 8 mm
- side wear plates - HB400

78 kg | CAT J200

RIPPER 6-12T

EFD





SPECIFICATION

- teeth model - CAT J250
- core S355 J2 ≠ 50 + 8 mm
- side wear plates - HB400

160 kg | CAT J250

RIPPER 12-18T

EFE

YouTube





SPECIFICATION

- teeth model -CAT J300
- core S355 J2 ≠ 60 + 16 mm
- side wear plates - HB400

234 kg | CAT J300

RIPPER SAW 1-1,9T

EFA-B



SPECIFICATION

- teeth model - CAT J200
- core S355 J2 ≠ 25 mm
- saw blade

40 kg | CAT J200

RIPPER SAW 1,9-3,5T

EFB-B



SPECIFICATION

- teeth model - CAT J200
- core S355 J2 ≠ 30 mm
- saw blade

54 kg | CAT J200

RIPPER SAW 3,5-6T

EFC-B



SPECIFICATION

- teeth model - CAT J200
- core S355 J2 ≠ 30 + 8 mm
- side wear plates - HB400
- saw blade

75 kg | CAT J200

RIPPER SAW 6-12T

EFD-B



SPECIFICATION

- teeth model - CAT J250
- core S355 J2 ≠ 50 + 8 mm
- side wear plates - HB400
- saw blade

168 kg | CAT J250

RIPPER SAW 12-18T

EFE-B



SPECIFICATION

- teeth model - CAT J300
- core S355 J2 ≠ 60 + 16 mm
- side wear plates - HB400
- saw blade

249 kg | CAT J300

GRADING BEAM 1,9-6T

EPA



190 - 216 kg





SPECIFICATION

- shaft diameter 178 mm
- bottom slides HB500 ≠ 8 mm
- adjustable working shaft height

INDEX	WIDTH	WEIGHT
EPA125	1250 mm	190 kg
EPA15	1500 mm	216 kg

GRADING BEAM 6-14T

EPB

319 - 335 kg





SPECIFICATION

- shaft diameter 245 mm
- bottom slides HB500 ≠ 10 mm
- adjustable working shaft height

INDEX	WIDTH	WEIGHT
EPB18	1800 mm	319 kg
EPB20	2000 mm	335 kg

GRADING BEAM 14-24T

EPC

YouTube

430 - 460 kg





SPECIFICATION

- shaft diameter 245 mm
- bottom slides HB500 ≠ 12 mm
- adjustable working shaft height

INDEX	WIDTH	WEIGHT
EPC22	2200 mm	430 kg
EPC25	2500 mm	460 kg

HYDRAULIC GRADING BEAM 1,9-6T

EPA-B





234 - 260 kg

37,5°

SPECIFICATION

- shaft diameter 178 mm
- bottom slides HB500 ≠ 8 mm
- tilt ±37.5°
- adjustable working shaft height

INDEX	WIDTH	WEIGHT
EPA125-B	1250 mm	234 kg
EPA15-B	1500 mm	260 kg

HYDRAULIC GRADING BEAM 6-14T

EPB-B





414 - 431 kg

44,5°

SPECIFICATION

- shaft diameter 245 mm
- bottom slides HB500 ≠ 10 mm
- tilt ±44,5°
- adjustable working shaft height

INDEX	WIDTH	WEIGHT
EPB18-B	1800 mm	414 kg
EPB20-B	2000 mm	431 kg

HYDRAULIC GRADING BEAM 14-24T

EPC-B





574 - 593 kg

36,5°

SPECIFICATION

- shaft diameter 245 mm
- bottom slides HB500 ≠ 12 mm
- tilt ±36.5°
- adjustable working shaft height

INDEX	WIDTH	WEIGHT
EPC22-B	2200 mm	574 kg
EPC25-B	2500 mm	593 kg

PALLET FORKS 1,6T

UPF16/12 M381







2 pcs	1600 kg	166 kg

SPECIFICATION

- 80x40x1200 2,0T FEM 2A fork
- 18 mm tool steel plate
- mechanical fork width adjustment

OPTIONS

- UPF16/10 - 80x40x1000 2,0T FEM 2A fork

PALLET FORKS 2,0T

UPF20/12 M382







2 pcs	2000 kg	189 kg

SPECIFICATION

- 80x40x1,200 2.0T FEM 2A fork as a standard
- 4 tapered bushings to attach the bale tine
- mechanical fork width adjustment

OPTIONS

- UPF20/10 - 80x40x1000 2T FEM 2A fork
- bale tine L-1100 M22
- bolt on protection frame



PALLET FORKS 2,5T

UPF25 M382







2 pcs.	2500 kg	241 kg

SPECIFICATION

- 100x40x1200 2,5T FEM 2A fork
- 4 tapered bushings to attach the bale tine
- mechanical fork width adjustment

OPTIONS

- bale tine L-1100 M22
- bolt on protection frame



PALLET FORKS 2,5T HYDRAULIC

UPF25H M382





2 pcs	2500 kg	270 kg

SPECIFICATION

- synchronous fork extension
- 100x40x1200 2,5 T fork as a standard

OPTIONS

- UPF25H-C hydraulic valve enabling side shifting
- flow divider valve - DFL - synchronized fork adjustment

	14 - 18 T	12 - 14 T	10 - 12 T	8,5 - 10 T
EB				
EE				
EK				
ED				
ES				
EF				

6-8,5 T | 5-6 T | 3,5-5 T | 2,6-3,5 T | 1,9-2,6 T | 1-1,9 T

For wheeled excavators, it is recommended to select attachments from a lower weight category than indicated by our scale, due to their greater dynamics and lower stability compared to tracked excavators.

NOTES

INFORMATION CLAUSE

All technical data given in this catalog refer to a specific product index, if accessories and optional items are not listed as standard, they are not included in machine composition. Photos of products may contain options and accessories that are not available in standard versions. Descriptions, dimensions, weights and technical data refer to the status of the machines on the day of creating the catalog, they are indicative and we reserve the right to make structural, visual and technical changes in connection with the adopted strategy of continuous product improvement. We cannot exclude differences between photos, dimensions, weights as well as errors in calculations or printout despite all efforts made to present a reliable offer. All machine weights are net weights not including the mounting and optional accessories, so it should be assumed that the final weight increase of approximately 10-200 kg. All calculations of volume and capacity were calculated assuming an error rate about 3% with the calculation method used by our company. We do not take responsibility for any irregularities in the catalog and they are not subject to complaint. All machines are tested under controlled conditions in terms of their functionality to perform specific tasks, for various reasons, the functioning of the machines may differ on the conditions in which it works.

Become an FK Machinery dealer

Let's build long-term value – together.

At FK Machinery, we work with dealers who want to deliver real performance and long-lasting value to their customers. We don't just sell equipment – we provide solutions that perform in the field, every day.

We are a European premium brand with Polish DNA and a business culture built on a practical approach. We are looking for partners who are ready to truly support their customers in choosing the right solutions and growing their business.

Our attachments are designed for efficiency in real working conditions, and our team supports your growth – not only with tools, but also with knowledge and trust.

FK Machinery®
BY KOŁASZEWSKI

POWER
in Precision Efficiency in Every Equipment

60
countries
Presence across Europe and all continents

50+
years of experience
Building quality since 1974

250+
attachment models
Wide product range for every need

600+
mounting options

95%
of customers come back for more
Highest level of customer satisfaction

Krzysztof Diks
+48 795 504 276
krzysztof@kolaszewski.com

Joanna Chamier Gliszczyńska
+48 721 555 258
joanna@kolaszewski.com

Karolina Myszka-Szynwelska
+48 798 323 130
karolina@kolaszewski.com

Artur Kupc
+48 798 981 464
artur@kolaszewski.com

+48 59 822 34 88
kolaszewski@kolaszewski.com
www.kolaszewski.com

Kołaszewski Sp. z o.o., ul. Lęborska 22, 77-100 Bytów, VAT ID: PL 842 168 26 56